

NU Series Insulation Piercing Connector



NU-1



NU-2



NU-3



NU-4

- The NU insulation piercing connectors are suitable to connect main and one, two tap conductors of section, how is written on NU body. Type without letter B serves to connect isolated conductors, with letter B bare conductors. NU for one tap conductor is equipped with cable termination cap PCEC16/120, for two output wires-no cap.
- NU consists from two glass-fiber reinforced plastic parts, which are fitted with two brass tinned teeth's, which are coated with UV-curing silica grease and the teeth are fitted with rubber insulation. This set is associated with the bolt, nut and pinch fixation segment.
- The terminals marked T are equipped with tear head. The lower part of the clamp is designed to chamber, providing optimal ventilation of NU
- Its self-seam frame is wet proof, water proof, and anti-corrosive, which can prolong the using life of insulated lead and connector.
- Designed for all weather applications and easy to install.
- NU had passed 6KV test under water for 1 Min.
- Standard: EN 50483-4, NFC 33-020, NFC 33-004

Item No.	Main wire section	Branch wire section	Bolt	Package(pcs)	Gross weight(kg)
NU-0	1-10	1-10	1	500	24
NU-1	10-95	1.5-10	1	500	24
NU-2	16-95	4-35	1	200	26
NU-3	50-150	6-35	1	200	27
NU-4	16-95	16-95	1	150	25.5
NU-5	35-150	35-150	1	150	27