

## DISCONNECT SWITCH

The ZR-Rotary Switch series is constructed from tough flame retardant ABS and are rated at IP65, making them suitable for the majority of internal and External applications. The Enclosed versions are fitted with several 22mm Gland knockouts and have Earth and Neutral bars fitted along with ample space inside for ease of installation.



## GENERAL CHARACTERISTICS

- Type: Disconnect switch
- Grounding: Non-Grounding
- Rated Voltage: 250V
- Rated Current: 10A/100A
- Application: Industrial
- Usage: Low Voltage
- Breaking Capacity: High
- Material: Copper
- Poles: 3P, 4P
- Rate current: 10A/16A, 20A, 32A, 40A, 50A, 63A, 80A, 100A
- Weather protected: IP65
- Easy cable access via M20/25 knockouts (top and bottom)
- Red/Yellow padlock
- Switch interlocked by lid to prevent opening in ON position
- Including earth terminals
- According to Standard: IEC-60947-3
- Certificate: CE, RoHS

## DIMENSIONS

Front



Side



Model	Rated Current	Enclosure Dimensions (mm)			Installation Dimensions (mm)		
		W	H	D	C	A1	A2
ZR15-20/3P	10A/16A/20A	80	100	65	35	60	90
ZR15-20/4P							
ZR15-32/3P	25A/32A	100	125	85	35	60	115
ZR15-32/4P							
ZR15-63/3P	40A/63A	114	175	100	35	60	165
ZR15-63/4P							
ZR15-100/3P	80A/100A	160	240	120	45	142	193
ZR15-100/4P							