

שעוני פיקוד מכניים יומיים

להתקנה על פס דין, למתח עבודה 16A/230V AC 50/60 Hz

מק"ט	תיאור המוצר	מגעים	סוללות גיבוי	רוחב מודול	זמן מיתוג	דגם
108014	יומי + מפסק 1-Auto	מגע פתוח	100 שעות	1	15 דקות	ELO-D
108023	יומי ורטיקלי + מפסק 1-0-2	מגע מחליף	100 שעות	2	15 דקות	BIO-D
108015	יומי + מפסק 1-0-2 + מחוגים	מגע מחליף	200 שעות	2	30 דקות	DUET-D
108016	יומי + מפסק 1-0-2 + מחוגים	מגע מחליף	200 שעות	3	15 דקות	ARVO-D

- תקנים: CE, IEC, CEE, UL
- הערות: סוללת גיבוי מסוג ליטיום (Lithium)
- מנגנון קוורץ

השעון
הנמכר
ביותר
בעולם



108014



108023



108015



108016

א.ר. אסקו יבוא ושיווק בע"מ

יבוא ושיווק חומרי חשמל לתעשייה | טל. 072-2114114 | פקס. 03-9641744 | WhatsApp. 054-4433230

שד' גן רווה 1, א.ת. צפוני יבנה, ת.ד. 13078 מיקוד 8122202

Electromechanical time switches

DUET


DIMENSIONS (mm)

CONNECTION DIAGRAM


Electromechanical time switches with daily or weekly programming by trippers for household use. The NiMH rechargeable battery allows a charge reserve of 150 hours and it can be replaced with ease once depleted by opening the front cover of the instrument.




- 1 Trippers for the programming of activation time
- 2 Switch for the choice of the operating mode
- 3 Dial for time and minutes regulation
- 4 Sealable cover
- 5 Container: 2 DIN modules
- 6 Battery drawer (for replacement)




Front view



Side view



Diagram



TIME AND MANAGEMENT

DAILY/WEEKLY TIME SWITCHES

- Power supply: 230Vac (-15% ÷ +10%)
- Output relays capacity: 16(4) A / 250 Vac
- Operating mode:
 - O** always OFF
 - A** automatic (according to the set programming with the trippers)
 - I** always ON
- NiMH battery (V80H type) rechargeable and replaceable by the front cover of the instrument
- Charge reserve of 150 hours



DUET-D

- daily programming
- 24 hours quadrant with 48 trippers
- every tripper covers 0.5 hours (30 minutes)



DUET-W

- weekly programming
- 7 days quadrant with 48 trippers
- every tripper covers 3.5 hours (210 minutes)

TECHNICAL INFORMATION

GENERAL CHARACTERISTICS

Power supply	V AC	230 (- 15% ÷ +10%)
Frequency	Hz	50 / 60
Absorption	W	0.5
Output relays capacity		16(4) A / 250 Vac
Operating precision		± 1 second/day at 23°C
Quadrant type		48 trippers
Minimum intervention time:	- DUET-D - DUET-W	30 minutes 3.5 hours (210 minutes)
Intervention precision:	- DUET-D - DUET-W	± 5 minutes ± 35 minutes
Charge reserve	h	150 (NiMH battery rechargeable and replaceable)
Operating temperature		-10 °C ÷ +45 °C
Class of protection		II
Degree of protection		IP20
Container		2 DIN modules

CONNECTABLE LOADS

Incandescent		3000 W
Fluorescent (neon)		1200 VA
Low voltage halogen		2000 VA
Halogen (230 V~)		3000 W
Low consumption (CFL)		1000 VA
Low consumption (CFL)		900 VA
Led		200 VA

Code	Model	Description
VP879100	DUET-D	Daily electromechanical time switch
VE125100	DUET-W	Weekly electromechanical time switch