

Product Fiche compliant to commission delegated regulation (EU) No 65/2014		
Brand	GORENJE	
Model	BDU 2116 AX	
EEI [%] Energy Efficiency Index - Main cavity ¹⁾		93.4
EEI [%] Energy Efficiency Index - Secondary cavity ¹⁾		109.7
Energy Efficiency Class - Main cavity ²⁾		A
Energy Efficiency Class - Secondary cavity ²⁾		B
Energy consumption in conventional mode [kWh/cycle] - Main cavity ³⁾		0.79
Energy consumption in conventional mode [kWh/cycle] - Secondary cavity ³⁾		0.79
Energy consumption in fan-forced mode [kWh/cycle] - Main cavity ³⁾		0.71
Energy consumption in fan-forced mode [kWh/cycle] - Secondary cavity ³⁾		
Energy consumption in conventional mode [MJ/cycle] - Main cavity ³⁾		
Energy consumption in conventional mode [MJ/cycle] - Secondary cavity ³⁾		
Energy consumption in fan-forced mode [MJ/cycle] - Main cavity ³⁾		
Energy consumption in fan-forced mode [MJ/cycle] - Secondary cavity ³⁾		
Number of cavities		2
Heat source - Main cavity		ELECTRICITY
Heat Source - Secondary cavity		ELECTRICITY
Usable volume [l] - Main cavity		50
Usable volume [l] - Secondary cavity		40
¹⁾ Energy Efficiency Index calculated according to the volume and energy consumption for each cavity.		
²⁾ From A+++ (low consumption) to D (high consumption).		
³⁾ Based on the results of standards tests that simulate the thermal properties of food. The consumption will depend on how the appliance is used.		

Product Information compliant to commission regulation (EU) No 66/2014			
	Symbol	Value	Unit
Model identification	BDU 2116 AX		
Type of oven	CONVENT/MULTIFUNCTIO		
Mass of the appliance	M	45.1	Kg
Number of cavities		2	
Heat source per cavity (electricity or gas)		2	
Volume per cavity - Main cavity	V	50	l
Volume per cavity - Secondary cavity	V	40	l
Energy consumption (electricity) required to heat a standardised load in a cavity of an electric heated oven during a cycle in conventional mode per cavity (electric final energy) - Main cavity	EC _{electric cavity}	0.79	kWh/cycle
Energy consumption (electricity) required to heat a standardised load in a cavity of an electric heated oven during a cycle in conventional mode per cavity (electric final energy) - Secondary cavity	EC _{electric cavity}	0.79	kWh/cycle
Energy consumption required to heat a standardised load in a cavity of an electric heated oven during a cycle in fan-forced mode per cavity (electric final energy) - Main cavity	EC _{electric cavity}	0.71	kWh/cycle
Energy consumption required to heat a standardised load in a cavity of an electric heated oven during a cycle in fan-forced mode per cavity (electric final energy) - Secondary cavity	EC _{electric cavity}		kWh/cycle
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Main cavity	EC _{gas cavity}		MJ/cycle kWh/cycle (a)
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Secondary cavity	EC _{gas cavity}		MJ/cycle kWh/cycle
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in fan-forced mode per cavity (gas final energy) - Main cavity	EC _{gas cavity}		MJ/cycle kWh/cycle
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in fan-forced mode per cavity (gas final energy) - Secondary cavity	EC _{gas cavity}		MJ/cycle kWh/cycle
Energy Efficiency Index per cavity - Main cavity	EEI _{cavity}	93.4	
Energy Efficiency Index per cavity - Secondary cavity	EEI _{cavity}	109.7	
(a) 1kWh/cycle = 3,6 MJ/cycle			