## product information sheet

Trade Mark	AEG	
Model	DLE0630B 942051288 ()	
Annual Energy Consumption (kWh/year)	0	
Energy Efficiency class		
Fluid Dynamic Efficiency	0	
Fluid Dynamic Efficiency class		
Lighting Efficiency (lux/W)	0	
Lighting Efficiency class		
Grease Filtering Efficiency	0	
Grease Filtering Efficiency class		
Air flow at minimum and maximum speed in normal use (m3/h)		
Air flow at intensive or boost setting (m3/h)	-	
Airborne acoustical A-weighted sound power emissions at minimum and maximum speed in normal use (dB(A))	/	
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	-	
Power consumption in off mode (W)	0	
Power consumption in standby (W)	0	

Attribute Name	Symbol	Value	Unit
Model Denomination		DLE0630B 942051288	
Annual Energy Consumption	AEChood	0,0	kwh/a
Time increase factor	f		
Fluid Dynamic Efficiency	FDEhood	0,0	
Energy Efficiency Index	EEIhood	0,0	
Measured air flow rate at best efficiency point	QBEP	,0	m3/h
Measured air pressure at best efficiency point	Рвер		Pa
Maximum air flow	Qmax	350,0	m3/h
Measured electric power input at best efficiency point	WBEP	0,0	W
Nominal power of the lighting system	WL	7,0	W
Average illumination of the lighting system on the cooking surface	Emiddle	0	lux
Measured power consumption in standby mode	Ps	0	W
Measured power consumption off mode	Po	0	W
Sound power level	Lwa		dB

EN 60704-2-13 - Household and similar electrical appliances – Test code for the determination of airborne acoustical noise – Part 2-13: Particular requirements for range hoods

EN 50564 - Electrical and electronic household and office equipment. Measurement of low power consumption

Suggestions for a correct use in order to reduce the environmental impact:

- Switch ON the hood at minimum speed when you start cooking and kept it running for few minutes after cooking is fi nished.
- Increase the speed only in case of large amount of smoke and vapour and use boost speed(s) only in extreme situations.
- Replace the charcoal filter(s) when necessary to maintain a good odour reduction effi ciency.
- Clean the grease filter(s) when necessary to maintain a good grease filter effi ciency.
- Use the maximum diameter of the ducting system indicated in this manual to optimize effi ciency and minimize noise.