

Energy Efficiency Information					
Attribute	Symbol	Value			Units
Model Identification		ECN62/72/92	ECP62/72/92	ECP92/102/112	
Annual Energy Consumption	$AEC_{Hood}$	60	60	60	kWh
Time increase factor	f	1.7	1.7	1.7	
Fluid Dynamic Efficiency	$FDE_{Hood}$	9.7	9.7	9.1	
Energy Efficiency Index	$EEl_{Hood}$	88.1	88.1	88.1	
Measured airflow at Best Efficiency Point	$Q_{BEP}$	227.7	227.7	219.2	$m^3/h$
Measured Pressure at Best Efficiency Point	$P_{BEP}$	141.0	141.0	137.0	Pa
Maximum airflow	$Q_{MAX}$	390.8	390.8	377.2	$m^3/h$
Measured electric power at Best Efficiency Point	$W_{BEP}$	92.2	92.2	91.61	W
Nominal lighting power	WL	4	4	4	W
Average illumination of the lighting system on the cooking surface	$E_{Middle}$	475	475	475	Lux
Measured power consumption in standby	$P_S$	N/A	N/A	N/A	W
Measured power consumption off mode	$P_O$	0.0	0.0	0.0	W
Sound power level	$L_{WA}$	60.0	60.0	60.0	dBA
Grease Filter Efficiency	$GFE_{Hood}$	71.4 (D)	71.4 (D)	76.7 (C)	%
Lamp efficiency	$LE_{Hood}$	118 (A)	118 (A)	118 (A)	%

E & O E. All instructions, dimensions and illustrations are provided for guidance only. CDA reserve the right to change specifications without prior notice.