

Energy Efficiency Information			
Attribute	Symbol	Value	Units
Model identification		EKN60, EKN70 & EKN90	
Annual Energy Consumption	AEC_{Hood}	62.9	kWh
Time increase factor	f	1.7	
Fluid Dynamic Efficiency	FDE_{Hood}	9.6	
Energy Efficiency Index	EEI_{Hood}	89.1 (D)	
Measured airflow at Best Efficiency Point	Q_{BEP}	181.8	m ³ /h
Measured pressure at Best Efficiency Point	P_{BEP}	184.0	Pa
Maximum airflow	Q_{MAX}	336.4	m ³ /h
Measured electric power at Best Efficiency Point	W_{BEP}	96.6	W
Nominal lighting power	WL	4	W
Average illumination of the lighting system on the cooking surface	E_{Middle}	488	Lux
Measured power consumption in standby	P_S	0.46	W
Measured power consumption off mode	P_O	N/A	W
Sound power level	L_{WA}	69.0	dBA
Grease Filter Efficiency	GFE_{Hood}	66.4 (D)	%
Lamp Efficiency	LE_{Hood}	122 (A)	%

E & O E. All instructions, dimensions and illustrations are provided for guidance only. CDA reserve the right to change specifications without prior notice.