







Neff N74TD00N0 Domino Teppan Yaki 40 cm Touch Control

Predeccessor:

Successor:

FAN code: 4242004188117 sales programme: N74TD00N0 396 mm

Control

TouchControl

Flexibility

- Stainless steel cooking surface
- 2 cooking zones

Special features

- Main switch
- Power on indicator light
- Temperature range 140 240 °C
- heating-up control
- Special level for keeping warm (70°C)
- Special level for cleaning (40°C)
- . LED display for each zone
- 2 stage residual heat indicators
- Count up timer
- LED timer for each zone with switch off function and acoustic signal
- Control panel suspension
- · Safety cut out facility
- Control panel lock
- ReStart function
- · Individual energy consumption display
- 2 spatulas included

Design

- · Ceramic glass on stainless steel trim
- Removable ceramic glass cover

Technical information

- Installation measurements (mm): 360 x 490-500
- 40 cm
- Length connecting cable 100 cm
- Min. worktop thickness: 30 mm
- Output 1900 W

Included accessories 2 x spatula

Optional accessories

• Z9914X0 Connecting strip

Technical Data

Characteristics

Product name/family : Vario/Domino Teppan Yaki

Construction type: Built-in Energy input : Electric Type of control: Electronic Grill grating material: N/A Required niche size for installation

(HxWxD): 90 x x

Width of the product (mm): 396

Dimensions of the product (mm): 90 x 396 x 546

Net weight (kg): 10.0 Gross weight (kg): 12.0

Residual heat indicator : Separate Basic surface material: N/A Color of surface : Stainless steel,

Stainless steel

Color of frame : Stainless steel Approval certificates: CE, VDE Length of electrical supply cord (cm):

100

EAN code: 4242004188117 Consumption and connection

features

Electrical connection rating (W): 1900 Current (A): 13

Voltage (V): 220-240 Frequency (Hz): 50; 60

Alternative colors available




N74TD00N0 396 mm



Domino combination options with corresponding appliance and cut-out measurements


Width type: 30 40 60 70 80 90 Appliance width: 306 396 606 708 826 918

| ABCDLX | | | | | |
|------------------|-----|-----|-----|-----|--------------------|
| 2x30 | 306 | 306 | - | - | 612 576 |
| 1x30, 1x40 | 306 | 396 | - | - | 702 666 |
| 1x30, 1x60 | 306 | 606 | - | - | 912 876 |
| 1x30, 1x70 | 306 | 708 | - | - | 1,014 978 |
| 1x30, 1x80 | 306 | 826 | - | - | 1,132 1,096 |
| 1x30, 1x90 | 306 | 918 | - | - | 1,224 1,188 |
| 2x40 | 396 | 396 | - | - | 792 756 |
| 1x40, 1x60 | 396 | 606 | - | - | 1,002 966 |
| 1x40, 1x70 | 396 | 708 | - | - | 1,104 1,068 |
| 1x40, 1x80 | 396 | 826 | - | - | 1,222 1,186 |
| 1x40, 1x90 | 396 | 918 | - | - | 1,314 1,278 |
| 3x30 | 306 | 306 | 306 | - | 918 882 |
| 2x30, 1x40 | 306 | 306 | 396 | - | 1,008 972 |
| 2x30, 1x60 | 306 | 306 | 606 | - | 1,218 1,182 |
| 2x30, 1x70 | 306 | 306 | 708 | - | 1,320 1,284 |
| 2x30, 1x80 | 306 | 306 | 826 | - | 1,438 1,402 |
| 2x30, 1x90 | 306 | 306 | 918 | - | 1,530 1,494 |
| 1x30, 2x40 | 306 | 396 | 396 | - | 1,098 1,062 |
| 1x30, 1x40, 1x60 | 306 | 396 | 606 | - | 1,308 1,272 |
| 1x30, 1x40, 1x80 | | 396 | 826 | - | 1,528 1,492 |
| 1x30, 1x40, 1x90 | 306 | 396 | 918 | - | 1,620 1,584 |
| 3x40 | 396 | 396 | 396 | - | 1,188 1,152 |
| 2x40, 1x60 | 396 | 396 | 606 | - | 1,398 1,362 |
| 1x30, 1x40, 1x70 | | 396 | 708 | - | 1,410 1,374 |
| 4x30 | 306 | 306 | 306 | 306 | 1,224 1,188 |
| 3x30, 1x40 | 306 | 306 | 306 | 396 | 1,314 1,278 |
| 2x30, 2x40 | 306 | 306 | 396 | 396 | 1,404 1,368 |
| 1x30, 3x40 | 306 | 396 | 396 | 396 | 1,494 1,458 |



measurements in mm

Domino combination options with corresponding appliance and cut-out dimensions (see table)



When installing several elements side by side, several assembly kits are also required (Z9914X0).

Cut-out dimensions (X) depending on the combination, see table:

measurements in mm