



CLS420

Column speaker

► Features

- Slim line ALU design
- Clear and crisp sound reproduction
- Mounting bracket included
- 4 x 3" drivers
- Different power taps
- Aluminum housing

► Applications

- Auditoria
- Houses of worship
- Sports facilities
- Conference facilities
- Public buildings
- Meeting rooms



The CLS series are standard powerful column speakers with a slim design, perfectly suitable for a wide variation of indoor applications where audibility of music and speech is very important.

The CLS420 features a speaker unit consisting of 4 x 3" drivers, capable of producing a power up to 20 Watt RMS.

The advanced technology gives the effect of listening to a single sound source, with the same dimensions of the total speaker unit. This guarantees a wide sound dispersion and improved speech intelligibility in acoustically difficult venues.

Some typical applications of column speakers are: houses of worship, auditoria, sports facilities, conference facilities, meeting rooms, public buildings, educational facilities, ...

It is fitted with a 100V line transformer with power taps for 20 W and 10 W.

The speaker housing is made of sturdy aluminium coated in a white color, offering a timeless design which will be appreciated in any interior.

For the mounting of the CLS420, a special bracket is included, which makes it possible to focus the speaker in any desired direction.

► Specifications

SYSTEM SPECIFICATIONS		
Speaker type		Column speaker
Max power		40 W
RMS power		20 W
Line transformer taps	1	20 W / 500 Ohm
	2	10 W / 1000 Ohm
Frequency response (± 3 dB)		170 Hz - 15 kHz
Sound Pressure (Max W/1m)		91 dB
Horizontal dispersion		115°
Vertical dispersion		30° off axis
PRODUCT FEATURES		
Dimensions (width x height x depth)		104 x 478 x 86 mm
Weight net		2,1 Kg
Drivers		4 x 3"
Connection		Screw terminal
Construction		Aluminium
Grill type		Aluminium grill
Mounting & handling		Mounting wall bracket
Available colours		CLS420/W White (RAL9001)
SHIPPING & ORDERING		
Packaging		Carton box
Shipping Weight & Volume		5,4 Kg - 0,0269 Cbm
Accessory Included		Wall mounting bracket
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products		