



# GEAR 300 LS 75W-90

**Lubricant for gearbox and limited slip differential  
integrated or not in the gearbox**

**100% Synthetic – Ester based**

## TYPE OF USE

Specially designed for the transmission of high performance and racing vehicles: Track, Rally, Rally Raid, electric vehicles transmission ...

All hypoid differentials with limited slip system, gearbox with integrated limited slip differential, mechanical transmission, synchronised or non synchronised gearbox, transfer gearbox operating under shocks, heavy loads and low revolution speed or moderate loads and high revolution speed when transmission efficiency as to be improved compare to a 75W-140 grade.

## PERFORMANCES

STANDARDS : **API GL-5**

100% synthetic extreme pressure lubricant for an efficient anti wear protection, a better resistance at high temperature and a longer life time.

Contains a special friction modifier to avoid noisy or dragging limited slip differential.

Very low shear loss by the severe test KRL 20H, thanks to the synthetic ester base with very high viscosity index (VI).

Very high lubricating power which decreases friction and wear.

Fluid at low temperature to allow easier gear shifting in cold conditions.

Less effort required on the gear lever to shift the gears.

Improved transmission efficiency compare to a 75W-140 grade.

Suitable for any type of seal and any type of material used in gearbox and limited slip differential design.

Anti-corrosion, Anti-foam.

## RECOMMENDATIONS

Oil change: According to manufacturers requirements and adjust according to your own use.

## PROPERTIES

Colour	Visual	Green
Viscosity grade	SAE J 306	<b>75W-90</b>
Density at 20°C (68°F)	ASTM D1298	0.904
Viscosity at 40°C (104°F)	ASTM D445	109.6 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	16.4 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	161
Flash point	ASTM D92	200°C / 392°F
Pour point	ASTM D97	-42°C / -43.6°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - TÉL : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Web Site : [www.motul.fr](http://www.motul.fr)

03/10