



DETAIL B B



Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

- Notes:
- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 - 2) 45° tapers have 1.5m spacing, no relaxations.
 - 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

SAFETY ZONE DIMENSIONS S	
Permanent speed limit 30mph or less	
Sideways safety zone	0.5m
Longways safety zone	0.5m
(Dimensions are minima)	

KEY

- Traffic sign
- Traffic cone
- No Parking Cone

Note. Whole promenade under 20mph speed limit
20mph signs not shown for clarity

QTY: 1 REF: 517 Road narrows on one side only ahead (variant)	
QTY: 3 REF: 7001 Road works ahead	
QTY: 1 REF: 778.1 Tramway level crossing	
QTY: 1 REF: 602 GIVE WAY sign	
QTY: 1 REF: 610 Keep left	
QTY: 2 REF: 610 Keep /right	
QTY: 2 REF: 517 Road narrows on one side only ahead	
QTY: 1 REF: 7011 When Stop Sign Shows Wait Here	
QTY: 1 REF: 7023 Stop Board	
QTY: 1 REF: 7024 Go Board	
QTY: 2 REF: 616 No entry	
QTY: 1 REF: 7010-1 Nature of temporary hazard ahead - Traffic Control Ahead	

Watling Streetworks
2 Premier Road
Ramsey, Isle of Man IM8 3AS

Promenade Refurbishment
Phase B SS1 - Cable
TMP
Client: Auldyn

Drawn By: DKW
Amendment: Proposed, 50m Added
Date: 28.08.19, 06.09.19

Traffic Management By

DRG Ref 2210.1.1
Area/ Road: Douglas Promenade

SCALE : Not to Scale DIMENSIONS : Metres