



DETAIL B (B)

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.
 Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.
 Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:
 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 2) 45° tapers have 1.5m spacing, no relaxations.
 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

SAFETY ZONE DIMENSIONS (S)
 Permanent speed limit 30mph or less
 Sideways safety zone 0.5m
 Longways safety zone 0.5m
 (Dimensions are minima)

KEY

- Traffic sign
- Traffic cone
- No Parking Cone
- Traffic signals to Diagram 3000.1
- Working Area
- Parking Suspended
- Pedestrian Barrier

QTY: 2 Keep right	REF: 610	
QTY: 1 Road narrows on one side only ahead	REF: 517	
QTY: 2 Road works ahead	REF: 7001	
QTY: 1 Lane closure barrier	REF: 7105	
QTY: 1 Road narrows on one side only ahead (variant)	REF: 517	
QTY: 1 Keep left	REF: 610	

Watling Streetworks Limited
 2 Premier Road
 Ramsey, Isle of Man IM8 3AS
 Telephone: 07624 495166
 Email: Doug@watlingstreetworks.com

Traffic Management
 HV Duct Install Phase 1
 Central Promenade
 Client: Auldyn

Drawn By DKW	Amendment Proposed	Date 20.08.19	Traffic Management By
-----------------	-----------------------	------------------	-----------------------



DRG Ref: 2246
 Area/ Road: Central Promenade
 SCALE : Not to Scale DIMENSIONS : Meters
 Reproduced from the Isle of Man Survey Map with the permission of the Department of Infrastructure
 Original drawing size A1 © Crown Copyright