



DETAIL B (B)



Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

- Notes:
- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 - 2) 45° tapers have 1.5m spacing, no relaxations.
 - 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

SAFETY ZONE DIMENSIONS (S)

Permanent speed limit 30mph or less
 Sideways safety zone 0.5m
 Longways safety zone 0.5m
 (Dimensions are minima)

KEY

- Traffic sign
- Traffic cone ● No Parking Cone
- 🚦 Traffic signals to Diagram 3000.1

Approx line of trench

MIN 3.25M

Watling Streetworks
 2 Premier Road
 Ramsey, Isle of Man IM8 3AS
 Telephone: 07624 495166
 Email: Doug@watlingstreetworks.com

Promenade Refurbishment
 HV Cable Laying
 Traffic Management
 Client: Auldyn

Drawn By	Amendment	Date
DKW	Proposed	25.10.19

Traffic Management By

DRG Ref: 3179
 Area/ Road: Loch Prom
 SCALE : Not to Scale DIMENSIONS : Metres
 Reproduced from the Isle of Man Survey Map with the permission of the Department of Infrastructure
 Original drawing size A1 © Crown Copyright