



**DETAIL B** (B)



Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

- Notes:
- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
  - 2) 45° tapers have 1.5m spacing, no relaxations.
  - 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

**SAFETY ZONE DIMENSIONS** (S)

Permanent speed limit 30mph or less  
 Sideways safety zone 0.5m  
 Longways safety zone 0.5m  
 (Dimensions are minima)

**KEY**

- Traffic sign
- Traffic cone ● No Parking Cone
- 🚦 Traffic signals to Diagram 3000.1

QTY: 1	REF: 804.4	
Parking place for solo motor cycles		
QTY: 1	REF: 801	
Parking place		
QTY: 2	REF: 606	
Turn right		
QTY: 2	REF: 610	
Keep left		
QTY: 1	REF: 517	
Road narrows on one side only ahead (variant)		
QTY: 1	REF: 7001	
Road works ahead		
QTY: 1	REF: 601-1	
Permanent STOP sign		

Watling Streetworks  
 2 Premier Road  
 Ramsey, Isle of Man IM8 3AS  
 Telephone: 07624 495166  
 Email: Doug@watlingstreetworks.com

Promenade Reconstruction  
 TT Bike Park  
 Traffic Management  
 Client: Auldyn

Drawn By	Amendment	Date
DKW	Proposed	17.10.18

Traffic Management By

DRG Ref: 2179B  
 Area/ Road: Gaiety Island  
 SCALE : Not to Scale DIMENSIONS : Metres  
 Reproduced from the Isle of Man Survey Map with the permission of the Department of Infrastructure  
 Original drawing size A1 © Crown Copyright