



Upholstered ottoman with steel sled base available in different finishes.

 0,28
  18,8
  1

	Seat height	Width	Depth
Measures mm.	420	800	800

Frame Sled base of 12 mm diameter steel rod. Polypropylene glides.

Seat Upholstered cushion with flexible fire resistant polyurethane foam with density between 25 kg/m³ and 40 kg/m³.

Other materials Zinc-nickel electrolyte screws. Polyvinyl acetate glue.

Accessories Polypropylene, felt or steel glides.

Leather

Leather

L1 High grade cow leather

L3 Polished full grain leather

L6 Aniline leather batique-effect. Scandinavian cattle.

Fabrics

Fabrics / Telas

1 Jacquard One
Jacquard Three
Sand
Era
Gravity
Rivet
Urban

2 Jacquard Two

3 Jacquard Four
Medley
Revive 1
Maglia
Main Line Flax
Loom Two

4 Jacquard 4 Special
Hemp
Nexus
Oxygen
Floyd
Remix 2
Heritage
Savane
Loom Three
Loom Four

5 Silk
Synergy
Step
Step Melange
Messenger 5
Blazer
Melange Nap
Glow

6 Capture
Fiord
Tonus 4
Divina 3
Lopi

7 Canvas 2
Rime


8 Capture
Fiord
Tonus 4
Divina 3
Lopi

9 Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

1 Valencia
2 Silvertex
4 Dolce
6 Ledger

Steel finish



Resistance and Quality

Indoor Air Quality-Advantage Gold
ISO 9001
UNE-EN 16139

Fireproof

BS 5852 Part 2 Crib 5
California Technical Bulletin 117
UNE-EN 1021-1 & 2
UNI 9175 (class 1 IM)

Sustainability

ISO 14001
ISO 14001
level® 2 certified to ANSI/BIFMA e3 Standard