





The CELLTRON™ Advantage Digital is a fast, user-friendly, premium handheld tester for measuring battery conductance, voltage, temperature and strap resistance in high-noise environments for a complete battery state-of-health analysis.

A COMPREHENSIVE BATTERY TESTING TOOL

With this lightweight handheld tester, users can guickly conduct a full battery performance assessment that can be uploaded wirelessly to the web-based UNITE™ database for centralized data storage, proactive maintenance planning, and compliance reporting.



ACCURATE CONDUCTANCE TESTING

The conductance-based diagnostics provided by the CELLTRON™ Advantage Digital delivers a highly accurate and reliable predictor of the battery's end of life.



HIGH NOISE IMMUNITY

The powerful dual-microprocessor architecture allows the tester to stand up to the high noise environments caused by UPS/battery systems and constant power supply switching (notorious for causing testers to fail).



DIGITAL SIGNAL FILTERING

Cleaner, more precise battery state-of-health measurements are achieved through new "Edge Rejection" technology which filters out anomalies that can corrupt battery signal readings at both the beginning and end of each sample signal.



WIRELESS COMMUNICATION

Built-in Wi-fi enables tester data to quickly and wirelessly be transmitted to and from the tester with no additional cards, cords, or hardware required. Users can pre-program battery string configuration details on their laptop and wirelessly upload to the tester.



SUPERIOR HARDWARE

Dual microprocessor signal filtering, integrated IR temperature measurement, built-in Wi-fi, USB communication port, and interchangeable light-up probe and clamp testing interfaces.



DEVICE & USER PROTECTION

A fast-acting protection relay responds in milliseconds when a signal input in excess of 23.3 volts is introduced through the testing probes, providing instant protection to both the device and the user.



FASTER TESTING TIMES

Testing is carried out in a matter of seconds simply by connecting the two test leads (either by clamp or probe) to the battery's positive and negative posts.



REMOTE BATTERY MANAGEMENT

The web-based UNITE™ software is a sophisticated database with advanced data visualization tools that accommodates Franklin's portfolio of industrial IoT devices. It enables users to wirelessly pre-program site string details, export the details to the tester, and upload battery test for analysis and reporting.



LONG-LASTING

An on-board battery pack is designed and tested for a full day of testing with 8 hours of service life per charge. The battery pack can be recharged directly through the tester or with a desktop charger.





HIGHLY CAPABLE

Conduct a variety of battery testing types, remotely configure the tester to your specifications, and manage and transfer data using the LCD screen. touch pad, and Wi-fi capability.

VOLTAGE: MEASURED:

RATED:

12.627

BATTERY GOOD

GENERATOR START

Test the state of health of generator starting batteries.

REPORTS

REPORTS

Generate reports for individual

battery string results.




SITE TRENDING Effective trend analysis including

test comparisons in one screen



BATTERY MANAGER

Select from a library of pre-loaded battery manufacturers and types.



DIGITAL MULTIMETER Accurately measure a battery's DC voltage.



QUICKTEST **QUICK TEST**

ITILITY

Start a test on a single cell or monoblock without setting up a site.



AUTOSTART Set the tester to activate a test process on contact.



Each kit comes complete with everything needed for testing, packaged in a ballistic nylon backpack with customized inserts fitted for the tester and accessories for easy transportation.



