

Low resistance testing

Megger has launched a new range of duplex test leads to give you more flexibility. Get one set of tester end leads and attach any of the selection of probes and clips to the tough duplex connector, one of which can house an LED indicator. Used with the DLRO10 series, the indicator will warn you about connections to hazardous live voltages, will indicate continuity and will let you know when the test is completed and if it passed or failed the pre-set test limit.



FAR END	TESTER END	USED WITH	TEST CURRENT	SPECIAL FEATURE	LENGTH	PART NO.
Male duplex connector	2 hooks and plug	DLRO10 DLRO10X, DLRO10HD				
	10 A					
	Indicator LED in connection	1.5 m	1006-456			
				Indicator LED in connection	3 m	1006-458
				Indicator LED in connection	6 m	1006-459
	2 hooks	DLRO10 DLRO10X, DLRO10HD				
	10 A		1.5 m	1006-452		
					3 m	1006-454
					6 m	1006-455
		BT51			3 m	1007-023
					6 m	1007-024
	Female duplex connector with locking ring	DLRO10 DLRO10X, DLRO10HD	10 A	Lead extension	6 m	1006-460
Duplex probe	Female duplex connector with locking ring	DLRO10 DLRO10X, DLRO10HD, BT51	10 A	P and C probe spacing 6 mm	0.4 m	1006-450
Right angle duplex probe				P and C probe spacing 10 mm	0.4 m	1006-449
Concentric duplex probe				P and C probe spacing 3.8 mm	0.4 m	1006-448
Kelvin clip				Clip capacity 40 mm	0.4 m	1006-447
Kelvin clip touch proof insulated				Clip capacity 52 to 75 mm	0.4 m	1006-451
Right angle duplex probe	2 hooks	BT51	10 A	In-line duplex locking connectors	3 m	1006-442
				In-line duplex locking connector	6 m	1006-443
Duplex probe	1 off 2 hooks and plug 1 off 2 hooks	DLRO10 DLRO10X, DLRO10HD	10 A	In-line duplex locking connectors, 1 with indicator LED	1.5 m	1006-444
Kelvin clip				In-line duplex locking connectors, 1 with indicator LED	3 m	1006-462
Kelvin clip touch proof insulated				In-line duplex locking connectors, 1 with indicator LED	3 m	1006-461
Heavy duty Kelvin 10 cm g-clamp	2 spades		100 A		5 m	242104-2-16
					8 m	242104-2-16
HD 60 mm current clips and 22 mm potential clips	2 hooks	DLRO100, DLRO200, DLRO600				
	600 A	25 mm 2 csa	5 m	1008-029		
				50 mm ² csa	5 m	1008-028
				70 mm ² csa	10 m	6220-756
				95 mm ² csa	15 m	6220-757