

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Cordless Combi

GSB 12V-35



Perfect balance between compactness, productivity and performance

The most important data

Torque (soft/hard/max.)	20/35/- Nm
No-load speed (1st gear / 2nd gear)	0 – 460 / 0 – 1,750 rpm
Battery voltage	12.0 V

Part Number 0 601 9J9 070

Technical data

Technical data

Torque (soft/hard/max.)	20/35/- Nm
No-load speed (1st gear / 2nd gear)	0 – 460 / 0 – 1,750 rpm
Battery type	Lithium-Ion
Max. impact rate	26,250 bpm
Chuck capacity, min./max.	0.8 / 10 mm
Battery voltage	12.0 V
Weight excl. battery	0.8 kg
Torque settings	20+1
Packaging dimensions (width x length x height)	360 x 444 x 122 mm
Battery capacity	3 Ah
Clamping range, min.	0.8 mm
Clamping range, max.	10 mm

Noise/vibration information

Drilling in metal

Vibration emission value ah	1.5 m/s ²
Uncertainty K	0 m/s ²

Impact drilling in masonry

Vibration emission value ah	14.5 m/s ²
Uncertainty K	1.5 m/s ²

Screwdriving

Vibration emission value ah	1.5 m/s ²
Uncertainty K	0 m/s ²

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Highest impact rate in the 12V category, enabling powerful impact drilling of up to Ø10 mm in masonry
- Compact design allows perfect handling and easy operation – even in challenging working situations
- High rotation speed of 1,750 rpm for a broad variety of jobs

