

Technical Data Sheet

Status
checked

24.07.2025
24.07.2025

Product **PureNight Pro ReNew**
PES-Dekotex mit "INKTeX+® FL Ausrüstung"
8668SDRNWGFS

Material 68 % Virgin polyester
32 % Textile-to-Textile chemically
recycled polyester - Level 5 -

Possible widths app. 310 cm

Making-up rolled on paper cores

Packaging Wrapped with foil (LDPE)

Ecology according to STANDARD 100 by OEKO-TEX,
product class 2
(direct contact with skin)

Recycling **Level 5 suitable / chemical recyclable**

Ink-type transfer printing,
direct printing with dye-sub inks

Properties Flame retardant, wrinkle resistant, blackout

Weight
acc. to DIN EN 12127 290.00 [g/m²] +- 3 [%]

Tearing strength

Elongation at 100 N, longitudinal direction
acc. to DIN EN ISO 13934-1 57.00 [%] +- 20 [%]

Elongation at 100 N, cross direction
acc. to DIN EN ISO 13934-1 1.65 [%] +- 20 [%]

Maximum tensile elongation, longitudinal
direction
acc. to DIN EN ISO 13934-1 90.00 [%] +- 20 [%]

Maximum tensile elongation, cross direction
acc. to DIN EN ISO 13934-1 28.00 [%] +- 20 [%]

Maximum tearing strength, longitudinal
direction (min.)
acc. to DIN EN ISO 13934-1 min. 125.00 [N/5 cm]

Maximum tearing strength, cross direction (min.)

acc. to DIN EN ISO 13934-1

min. 25.00 [N/5 cm]

We do not accept liability for errors. The confirmed properties are valid in the state of delivery. Any further processing can change them (e.g. washing / flame retardancy).

Please pay attention to our general considerations regarding fabrication at www.g-o-friedrich.com

Printing mistakes and changes are reserved.