

MOTOTRBO ION

YOUR BUSINESS RUNS ON VOICE AND DATA.
BUT IF YOUR DEVICES CAN ONLY ACCESS ONE,
YOU'RE NOT RUNNING AT YOUR BEST.



MOTOTRBO™ Ion is our first business-ready communication device with always-on voice and broadband data capabilities. It brings together renowned PTT performance, an open app ecosystem on the Android platform, and access to our unified technology ecosystem – from video security and analytics solutions, to best-in-class network security, to powerful new software and technology services like smart virtual assistants.

With MOTOTRBO Ion, teams stay connected across networks and devices. Business-critical data and workflows are unified and simplified, and the capabilities that your workforce needs to be at their best are always on.

KEY FEATURES

APPS ARE ON

- Android platform
- Open app ecosystem
- Motorola Solutions' unified technology ecosystem
- Full multimedia capabilities
- Intuitive touchscreen interface

UPTIME IS ON

- Fast setup and updates
- Seamless device management
- Managed and supported services

SECURITY IS ON

- Device security
- Application security
- Data security

DEPENDABILITY IS ON

- Built for any environment
- Industry-leading audio
- Ultra-rugged touchscreen
- Customisable experience
- Long battery life
- Redesigned antenna
- TIA4950 intrinsically safe

CONNECTIVITY IS ON

- Dedicated PTT device
- Seamless Voice Handover
- Full network interoperability with WAVE PTX™
- Digital Mobile Radio (DMR)
- 4G LTE
- Wi-Fi
- Wi-Fi Hotspot
- Bluetooth®
- 3G and 4G LTE cellular telephony
- HD Voice



FEATURES

CONNECTIVITY

LTE	B1, B2, B3, B4, B5, B7, B8, B20, B28, B38, B39, B40, B41
Bands Supported	UMTS: 850 MHz, 900 MHz, 1700 MHz, 1900 MHz, 2100 MHz
Device Class	4

DMR (MOTOTRBO)

Operational Systems	Digital and Analogue Modes, Conventional, Dual Capacity Direct Mode, IP Site Connect, Capacity Plus (Single- and Multi-Site), Capacity Max
Frequency Bands	UHF (400 -527 MHz) Up to 1000 Channels Up to 250 Zones
Channel Spacing	12.5, 20, 25 kHz

DMR TRANSMITTER SPEC

RF Output Power	4 W (high) / 1 W (low)
4FSK Digital Modulation	12.5 kHz Data: 7K60F1D and 7K60FXD 12.5 kHz Voice: 7K60F1E and 7K60FXE Combination of 12.5 kHz Voice and Data: 7K60F1W
Digital Protocol	ETSI TS 102 361, DMR Tier II & III
Conducted/Radiated Emissions (ETSI)	-36 dBm < 1 GHz, -30 dBm > 1 GHz
Adjacent Channel Power	60 dB (12.5 kHz channel), 70 dB (20/25 kHz channel)
Frequency Stability	± 0.5 ppm

DMR RECEIVER SPEC

Analogue Sensitivity (12dB)	0.16 uV
Digital Sensitivity (5% BER)	0.14 uV
Intermodulation (TIA603D)	70 dB
Adjacent Channel Selectivity, (TIA603A)-1T	60 dB (12.5 kHz channel), 70 dB (20/25 kHz channel)
Adjacent Channel Selectivity, (TIA603D)-2T	45 dB (12.5 kHz channel), 70 dB (20/25 kHz channel)
Spurious Rejection (TIA603D)	70 dB

Wi-Fi

Standards Supported	802.11 a/b/g/n/ac
Frequency Range	2.4 GHz, 5 GHz
Security	Supports WEP, WPA, WPA2, WPA3, Wi-Fi Enhanced Open

BLUETOOTH

Version	5.0 + LE +BR / EDR
Range	Class 1.5, 10m
Simultaneous Connections	1 x audio accessory and 1 x data device

GNSS SPECIFICATIONS

Time To First Fix, Cold Start	< 50 sec
Time To First Fix, Hot Start	< 5 sec
Horizontal Accuracy	< 5 m

LOCATION TRACKING

Built-in GNSS (GPS / GLONASS / BEIDOU / GALILEO) and AGPS
Indoor Positioning

BATTERY

Technology	IMPRES™ 2 Smart Battery
Battery Capacity	Standard 2820 mAh Standard HazLoc 2900 mAh
Power Supply	7.5 (Nominal)

AUDIO

Audio Output Power	Rated: 1 W @ 1% distortion Maximum: 3 W
Audio Response (EIA)	+1, -3 dB
Hum and Noise	-40 dB (12.5 kHz channel) -45 dB (20/25 kHz channel)
Conducted Spurious Emissions (TIA603D)	-57 dBm
Audio Features	Adaptive Speaker Equalisation Adaptive Dual Microphone Noise Suppression Adaptive Gain Control Adaptive Wind Noise Mitigation Automatic Acoustic Feedback Suppression Intelligent Audio IMPRES Audio Microphone Distortion Control User-Selectable Audio Profiles Trill Enhancement
Voice Interaction	Customisable Voice Announcements Voice Control: 13 Actions with Intuitive Commands

SOFTWARE

Operating System	Android 11
Google Certifications	Google Mobile Services Android Enterprise Recommended

VIDEO AND IMAGING

Supported Formats	H.263, H.264, MPEG-4 SP, VP8, JPEG (.jpg), GIF (.gif), PNG (.png), BMP (.bmp), WebP, (.webp) formats supported for playback, streaming, and recording
Supported File Types	3GPP (.3gp), MPEG-4 (.mp4), WebM (.webm), (.mkv)
Video Recording Quality	1080p (FHD) at 30 fps

SECURITY

Root Detection: Standard
Multi-Factor Authentication: Optional
Integrity Monitoring: Standard
Malware Blocking: Standard
Secure boot: Standard
Mobile Virtual Private Network: Optional

SPECIFICATIONS

HARDWARE

Main Display	102 mm colour display, 480 x 800 px Capacitive touchscreen with Gorilla Glass Usable with gloves up to 4 mm thick Resistant to false actuation from fresh or salt water, snow, dirt or grease
Top Display	27 mm Monochromatic LCD
Memory	4 GB RAM 64 GB ¹ Internal Storage Storage is expandable with external up to 256 GB microSD™ card
Card Slot	eSIM ¹ 1 x Nano SIM, 1 x Micro SD
Camera	Rear 13 MP High-Output LED Flash Auto Focus 8x Digital Zoom
Sensor Platform	Hall-Effect Sensor Barometer Ambient Light Sensor Gyroscope Accelerometer E-Compass
User Interface	High velocity user interface: large touch targets, shallow menu hierarchy, home screen information at a glance.
Physical Buttons	Dedicated PTT Button Dedicated Emergency Button 3 Programmable Buttons Power/Volume Knob Display On/Off Button Channel Selector
Antenna Length	6 cm or 9 cm, depending on frequency. Please refer to the MOTOTRBO Ion Accessory Catalogue for details.

HAZLOC PROTECTION

When properly equipped with Motorola UL-Approved battery, MOTOTRBO Ion is UL Approved to TIA-4950 for use in Hazardous Locations, Division 1, Class I, II, III, Groups C, D, E, F, G; Division 2, Class 1, Groups A, B, C, D, T3C. Tamb = -20 °C to +60 °C.

PHYSICAL²

Dimensions (H x W x D) with Standard Battery	143 mm x 70 mm x 29 mm
Dimensions (H x W x D) with Standard Hazloc Battery	143 mm x 70 mm x 38 mm
Weight with Standard Battery	414 g
Weight with Standard Hazloc Battery	439 g

RUGGEDNESS

Ingress Protection	IP68 (2 metres, 2 hours)
--------------------	--------------------------

¹ "B" revision hardware has 64 GB internal storage and eSIM. Earlier models had 32 MB internal storage and no eSIM.

² Physical specifications and dimensions are listed without antenna.



ENVIRONMENTAL AND REGULATORY

MIL-STD 810

	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G	
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.
Low Pressure	500.1	I	500.2	I/II	500.4	I/II	500.6	I/II	500.6	I/II
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.4	I/Hot, II/Hot	501.6	I/A1, II/A1	501.7	I/A1, II/A1
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.4	I/C3, II/C1	502.6	I/C3, II/C1	502.7	I/C3, II/C1
Temperature Shock	503.1	I	503.2	I/A1, C3	503.4	I	503.6	I/C	503.7	I/C
Solar Radiation	505.1	II	505.2	I/Hot-Dry	505.4	I/Hot-Dry	505.6	I/A1	505.7	I/A1
Rain	506.1	I, II	506.2	I, II	506.4	I, III	506.6	I, III	506.6	I, III
Humidity	507.1	II	507.2	II/Hot-Humid	507.4	-	507.6	II/Aggravated	507.6	II/Aggravated
Salt Fog	509.1	I	509.2	I	509.4	-	509.6	-	509.7	-
Dust	510.1	I	510.2	I, II	510.4	I, II	510.6	I, II	510.7	I, II
Vibration	514.2	VIII/F, W, XI	514.3	I/10, II/3	514.5	I/24, II/5	514.7	I/24, II/5	514.8	I/24, II/5
Shock	516.2	II	516.3	I, IV	516.5	I, IV	516.7	I, IV	516.8	I, IV
Contamination by Fluids							504.2	II	504.3	2.2.6 b

ENVIRONMENTAL

Operating Temperature	-20 to +60 °C (-4 to +140 °F)
Storage Temperature	-40 to +85 °C (-40 to +185 °F)
Humidity	Per MIL-STD 810
Thermal Shock	Per MIL-STD 810
Electrostatic Discharge	IEC 61000-4-2 Level 4
Dust and Water Intrusion	IEC 60529 - IP68, 2 m for 2 hrs
Salt Fog	5% NaCl for 48 hrs at 35 °C, 48 hrs standing
Packaging Test	Per MIL-STD 810

REGULATORY

Model Number	MSLB-MKZ900i
--------------	--------------

For more information, please visit motorolasolutions.com/ion



Motorola Solutions UK Ltd, Nova South, 160 Victoria Street, London, SW1E 5LB.

Availability is subject to individual country law and regulations. All specifications shown are typical unless otherwise stated and are subject to change without notice.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2023 Motorola Solutions, Inc. All rights reserved. (03-23)