

SR WINCH SERIES STANDARD SLEW RING



RED ROOSTER LIFTING

STANDARD FEATURES

- ▷ Heavy duty slew ring
- ▷ Heavy duty planetary gearboxes fitted with pinions
- ▷ SR E IP 54 400 V AC / 3-phases / 50 Hz braked motors
- ▷ SR H orbit or radial piston type hydraulic motor complete with brake valve
- ▷ Steel drum with cable fixing point at flange
- ▷ Double layer 2-component conservation according ISO 12944 category C2-Low, colour RAL 5010
- ▷ FEM / ISO class: T3-L3-M4

AVAILABLE CONTROL OPTIONS

- ▷ Control box IP 55 with pushbuttons and emergency stop built acc. to NEN 1010
- ▷ Control box IP 66 with low voltage IP 65 remote control built acc. to NEN 1010
- ▷ Load limiter (required by CE for applications exceeding 1000 kg WLL)
- ▷ Frequency inverter for speed control
- ▷ Wireless radio remote control systems
- ▷ Limit switches
- ▷ Slack wire switches
- ▷ Proportional local or remote control valve

AVAILABLE OPTIONS

- ▷ IP 56 TENV cast iron motors
- ▷ Explosion-proof motors
- ▷ Protective steel motor cover
- ▷ Band brakes (manual or fail-safe automatic)
- ▷ Alternative speeds
- ▷ Alternative supply voltages
- ▷ Drum guards
- ▷ Spooling gears
- ▷ Grooved drums
- ▷ Slip ring or swivel mounting
- ▷ Alternative drum dimensions / split drums / additional rope anchors / etc.
- ▷ Warping head
- ▷ Marine / offshore coating systems
- ▷ Tubular offshore frame with lifting eyes



Image for illustration purposes only

MODEL	WLL 1st LAYER KG	WLL 5th LAYER KG	RECOMMENDED ROPE DIA MM	SPEED 1st LAYER M/MIN	SPEED 5th LAYER M/MIN	DRUMCAP 1st LAYER M	DRUMCAP 5th LAYER M	MOTOR POWER kW
SR 30 E3	43000	30000	44	7	10	42	290	66
SR 40 E3	57000	40000	52	6	8	40	290	66
SR 50 E4	73000	50000	56	6	8	37	275	74
SR 30 H3	41000	30000	44	7	10	42	290	66
SR 40 H3	57000	40000	52	6	8	40	290	66
SR 50 H4	73000	50000	46	6	8	37	275	74

Information subject to change without notice

RED ROOSTER LIFTING

Nauta House, The Meadows
Oldmeldrum, Aberdeenshire
United Kingdom, AB51 0EZ

T: +44 (0) 1651 872101
E: sales@redroosterlifting.com
W: www.redroosterlifting.com