

DLR-1250 WINCH DIVER LAUNCH & RECOVERY



RED ROOSTER
LIFTING

STANDARD FEATURES

- ▷ Compact units with minimal deck space usage
- ▷ Suitable for Sea state 2-3
- ▷ Easily rigged and set up
- ▷ Main diving bell winch OHR 1.5, WLL 1250 kg @ 40 m/min
- ▷ Clump weight winch OHR 1.5, WLL 1250 kg @ 40 m/min
- ▷ Limit switches for upper limit
- ▷ Double fail-safe braking on both winches
- ▷ Lifting height (lowering depth) 90 metres
- ▷ Utility winch 500 kg @ 25 m/min. (optional)
- ▷ Fleet angle compensators for winches
- ▷ Power supply: 380-460 V AC, 50/60 Hz
- ▷ Hydraulic cylinders for deploying the A-frame (optional)
- ▷ Forklift pockets for easy handling
- ▷ Container sockets for easy fastening
- ▷ Welding brackets for deck mounting
- ▷ Readout unit of paid-out wire rope
- ▷ HPU Eexd ATEX, 100 l/min. @ 180 bar, redundant pump system and cross-over manifold and quick release connections
- ▷ Hydraulic proportional valves for winches and A-frame operation
- ▷ Operating conditions -20°C to 50°C
- ▷ Full material traceability (3.1 - EN 10204) on load-bearing parts
- ▷ Easy transportation because it fits a standard 20" container size
- ▷ Fitted with twist-free wire ropes with high (10x) safety factors
- ▷ IMCA and Lloyds compliant
- ▷ Flood light, Eexd
- ▷ Standard open basket with bottle mounting bracket, fall-out prevention, pay load 650 kg
- ▷ Clump weight: 400 kg
- ▷ Dimensions; operational 2976 x 2502 x 4017 mm, collapsed 4558 x 2178 x 1111 mm
- ▷ Weight excl. HPU; 2750 kg.



Image for illustration purposes only

RED ROOSTER LIFTING

Nauta House, The Meadows
Oldmeldrum, Aberdeenshire
United Kingdom, AB51 0EZ

T: +44 (0) 1651 872101
E: sales@redroosterlifting.com
W: www.redroosterlifting.com