

GUYSON TURBOLLOY

for use with turbine wheel and dry compressed air systems

GENERAL

Guyson Turbolloy is a specially produced cut wire product manufactured from brass wire. There are limited applications and this product is not specified very often, partly due to its high cost.

Turbolloy would generally be used in wheel/turbine or pressure blast systems, but is still effective when used in suction feed systems.

TYPICAL APPLICATIONS

Treatment of copper or brass components to give a bright sheen finish after forging or forging prior to further finishing processes such as plating or polishing

Physical Composition

Cut brass wire

Size Available : 500 micron

Pack Size : 25 kg bag

Physical Data

Shape : Cut wire pellet
Colour : Brass / Metallic
Density : 8.5 g/cc (approx)

Turbolloy is a non-toxic and non-hazardous product. No special disposal precautions are required for the product once it has been used for blast finishing applications. However, contamination from a specific application or process must also be considered prior to disposal

See Guyson MSDS reference 46 for all other details

Guyson International Limited
Snaygill Industrial Estate Keighley Road ▪ SKIPTON ▪ North Yorkshire ▪ BD23 2QR

Tel: +44 (0) 1756 799911 ▪ E-mail: info@guyson.co.uk ▪ Website: www.guyson.co.uk

Manual Blast Systems ▪ Semi/Fully Automated Blast System ▪ Robotic Blast Systems
Ultrasonic Baths and Tanks ▪ Multi-Stage Aqueous Ultrasonic Systems ▪ Mono and Co-Solvent Cleaning Systems
Rotary Basket Spray Wash Systems ▪ Spare Parts / Blast Media ▪ Service