

# SALONI

| <b>MODEL:</b> Robur Gris Antideslizante 24,8x100         |  |                                      |
|--|--|--------------------------------------|
| <b>BRAND:</b> SALONI                                     | <b>CODE:</b> HHA710                            | <b>EDITION:</b> 1                    |
| <b>CLASSIFICATION (UNE-EN-14411):</b> Grupo BIa. Anexo G |  | <b>DECLARATION OF BENEFITS:</b> 03DP |
| STANDARD   | CHARACTERISTICS                                | TEST RESULT                          |
| UNE-EN ISO 10545-3                                       | Water absorption                               | E < 0,5%                             |
| UNE-EN ISO 10545-4                                       | Breaking strength (N)                          | 2500                                 |
| UNE-EN ISO 10545-4                                       | Modulus of rupture (N/mm <sup>2</sup> )        | 47                                   |
| UNE-EN ISO 10545-6                                       | Resistance to deep abrasion (mm <sup>3</sup> ) | 130                                  |
| UNE-EN ISO 10545-7                                       | Abrasion resistance                            |                                      |
|  | Class  |                                      |
|  | Stage  | Rev.                                 |
| UNE-EN ISO 10545-9                                       | Thermal shock resistance                       | Ok                                   |
| UNE-EN ISO 10545-11                                      | Resistance to crazing                          | O.k.                                 |
| UNE-EN ISO 10545-12                                      | Frost Resistance                               | Resist                               |
| UNE-EN ISO 10545-13                                      | Chemical Resistance                            |                                      |
|  | Household Chemicals                            | A                                    |
|  | Swimming pool salts                            | A                                    |
|  | Citric Acid                                    | LA                                   |
|  | Lactic Acid                                    | HA                                   |
|  | Hydrochloric Acid low concentrations           | LA                                   |
|  | Hydrochloric Acid high concentrations          | HA                                   |
|  | Potassium Hydroxide low concentrations         | LA                                   |
| Potassium Hydroxide high concentrations                  | HA   |                                      |
| UNE-EN ISO 10545-14                                      | Resistance to staining                         |                                      |
|  | Fe2O3 / Cr2O3                                  | Class 5                              |
|  | Iodine / alcohol solution                      | Class 5                              |
|  | Light oil                                      | Class 5                              |
| UNE-41901:2017 EX  | Slip Resistance                                | C3                                   |
| <b>Dimension (mm)</b>                                    | 248X1000                                       | <b>Thickness (mm)</b> 9,8            |
| <b>Classification according to Saloni quality:</b>       |  | D                                    |

This document is for commercial and informational use. Saloni reserves the right to modify or eliminate any information contained in it.  
In case of doubt, please verify the data of this technical sheet with the factory.

Printing date: 05/03/2020



Cerámica Saloni S.A.U.  
[www.saloni.com](http://www.saloni.com)

# DECLARACIÓN DE PRESTACIONES (DECLARATION OF PERFORMANCE)

Nº. 03DP

## 1.- Código de identificación única del producto tipo:

### Unique identification code of the product-type:

Baldosa cerámica prensada en seco, con absorción de agua  $E_b \leq 0.5\%$

Dry-pressed ceramic tiles, with water absorption  $E_b \leq 0.5\%$

## 2.- Usos previstos:

### Entended use/es:

Para suelos y paredes interiores y exteriores

For internal and external floorings and walls

## 3.- Fabricante:

### Manufacturer:

Cerámica SALONI, SAU

Ctra. Alcora, Km. 17

12130 San Juan de Moró, Spain

www.saloni.com

## 4.- Sistema de evaluación y verificación de la constancia de prestaciones (EVCP):

### System/s of assessment and verification of constancy of performance (AVCP):

Sistema 4

System 4

## 5.- Norma armonizada:

### Harmonised standard:

EN 14411:2012

## 6.- Organismo notificado:

### Notified body/ies:

No aplica

Not apply

## 7.- Prestaciones declaradas:

### Declared performances:

| Características esenciales<br>Essential Characteristics   | Prestaciones<br>Performance                                      |
|---|--|
| <b>Reacción al fuego</b><br>Reaction to fire  | A1 <sub>FL</sub> /A1   |
| <b>Emisión de sustancias peligrosas:</b><br>Release of dangerous substance, for:<br>Cadmio (Cadmium)<br>Plomo (Lead)    | PND<br>PND   |
| <b>Fuerza de rotura</b><br>Breaking strength  | $e < 7.5 \geq 700 \text{ N}$<br>$e \geq 7.5 \geq 1300 \text{ N}$ |
| <b>Deslizamiento</b><br>Slipperiness  | PND  |
| <b>Propiedades táctiles</b><br>Tactility  | PND  |
| <b>Adhesión, para:</b><br>Bond strength/adhesion, for:<br>Adhesivo cementoso tipo C2 (Cementitious adhesive, type C2)   | $> 1 \text{ N/mm}^2$   |
| <b>Durabilidad para:</b> usos interiores<br>Durability for: internal use  | Cumple (Pass)  |
| <b>Durabilidad para usos exteriores:</b> resistencia a la helada<br>Durability for external use: freeze-thaw resistance | Cumple (Pass)  |
| <b>Resistencia al choque térmico</b><br>Thermal shock resistance  | Cumple (Pass)  |

Las prestaciones del producto identificado anteriormente son conformes con el conjunto de prestaciones declaradas. La presente declaración de prestaciones se emite, de conformidad con el Reglamento (UE) nº 305/2011, bajo la sola responsabilidad del fabricante arriba indicado.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of conformity is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Firmado por y en nombre del fabricante por:

Signed for and on behalf of the manufacturer by:

Rafael Prats García

En/At San Juan de Moró el/on 01/09/2015

Firma/Signature