

-----  
SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION  
-----

## CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT CODE. . . . : 11242 061765 604  
PRODUCT NAME . . . : 110283 CANDLE MOLD RELEASE  
PRODUCT CLASS . . . : Aerosol Product

MSDS PREPARATION DATE : 02/16/2006

## MANUFACTURER IDENTIFICATION:

## CUSTOMER IDENTIFICATION:

Yaley Enterprises  
7664 Avianca Drive

Redding

CA 96002

## EMERGENCY TELEPHONE NUMBERS:

24 HOURS A DAY - CALL CHEMTREC : 800-424-9300  
INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887  
8 AM TO 4:30 PM CENTRAL TIME : 262-255-9500

-----  
SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS  
-----

## 1 N-BUTANE

CAS# 106-97-8

## N-BUTANE

PCT BY WT: 14.0000 VAPOR PRESSURE: 879.100 MMHG @ 68F LEL 1.80

## EXPOSURE LIMIT:

ACGIH TLV-TWA 800 ppm  
ACGIH TLV-STEL NO INFO  
OSHA PEL-TWA 800 ppm  
COMPANY N.E.

-----  
2 PROPANE

CAS# 74-98-6

## PROPANE

PCT BY WT: 18.0000 VAPOR PRESSURE: 5585.200 MMHG @ 68F LEL 2.20

## EXPOSURE LIMIT:

ACGIH TLV-TWA 1000 ppm  
ACGIH TLV-STEL NO INFORMATION

-----  
3 HEPTANE

CAS# 142-82-5

## HEPTANE

PCT BY WT: 66.0000 VAPOR PRESSURE: 45.000 MMHG @ 68F LEL 1.10

## EXPOSURE LIMIT:

ACGIH TLV-TWA 400 ppm  
ACGIH TLV-STEL 500 ppm  
OSHA PEL-TWA 400 ppm  
COMPANY N.E.

MATERIAL SAFETY DATA SHEET

11242 061765 604

-----  
-----  
\*\*\*\*\*  
This product contains no reported carcinogens or suspected  
carcinogens.  
\*\*\*\*\*  
-----

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Extremely flammable liquid and vapor.  
Vapors may cause flash fire or explosion.  
Extremely flammable aerosol.  
Contents under pressure.

EYE:

May cause eye irritation.

SKIN:

May cause skin irritation.  
Material may aggravate an existing dermatitis.

INHALATION:

Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.  
Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.  
Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.  
Repeated overexposure may aggravate or enhance existing nervous dysfunction produced by disorders known to cause nervous system damage such as diabetes, alcohol and drug abuse, & Parkinson's disease.

INGESTION:

CHRONIC EFFECTS:

SECTION 4 - FIRST AID MEASURES

EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN CONTACT:

Wash thoroughly with soap and water and seek medical attention if irritation persists. Remove contaminated clothing. Launder contaminated clothing before reuse.

INHALATION:

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

INGESTION:

Do not induce vomiting which can cause chemical pneumonitis and pulmonary edema. Contact a physician immediately.

MATERIAL SAFETY DATA SHEET

11242 061765 604

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

Flashpoint . . . . . : Less Than -25 °F  
Explosion Level . . . . . : Low (LEL) - 1.1  
High (UEL) - 9.5

EXTINGUISHING MEDIA:

Use Dry Chemical, Carbon Dioxide or Chemical Foam.

FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Contents under pressure. Do not use or store near sources of heat, sparks or open flame. Keep away from any source of heat such as sunlight, heaters or stoves that could cause the container to burst. Do not puncture or incinerate. Do not crush or place in a garbage compactor. Do not store above 120 degrees F. Aerosol containers may explode when exposed to extreme heat. Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back. Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used. Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CLEAN-UP AND CONTAINMENT:

Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire. Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials and non-sparking tools.

SECTION 7 - HANDLING AND STORAGE

HANDLING:

Wash hands thoroughly after handling.

STORAGE:

Store in a cool dry area with ventilation suitable for storing materials shown in section 2. Keep away from heat, sparks and flame. Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

ENGINEERING CONTROLS:

# MATERIAL SAFETY DATA SHEET

11242 061765 604

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

## RESPIRATORY PROTECTION:

If workplace exposure limits are exceeded for any component (see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

## SKIN PROTECTION:

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

## EYE PROTECTION:

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

## OTHER PROTECTIVE EQUIPMENT:

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

## HYGIENIC PRACTICES:

Wash hands before eating or smoking. Smoke in designated areas only.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure	5585.20	mm Hg @ 20 C
Vapor Density	-N/A	
Boiling Range	Lower - 1.0 °F Higher - 209.0 °F	
Specific Gravity	.638	
Formula Weight per Volume	5.3154	LB/GL
VOC (Calculated, LB/GAL)	5.183	
VOC (Calculated, GM/L)	621.07	
Percent Volatile by Weight	97.5006	
Percent Volatile by Volume	98.4236	
Evaporation Rate	4.500	(n-Butyl Acetate = 1)
Viscosity	-N/A	

## SECTION 10 - STABILITY AND REACTIVITY

### CONDITIONS TO AVOID:

Avoid contact with heat, sparks, and open flame.  
Product may explode if heated. Keep cool, avoid exposure to heat.

### INCOMPATIBILITIES:

Strong oxidizing agents.

### DECOMPOSITION:

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

### POLYMERIZATION:

No hazardous polymerization will occur under normal conditions.

### STABILITY:

The product is stable under normal storage conditions.

MATERIAL SAFETY DATA SHEET

11242 061765 604

SECTION 11 - TOXICOLOGICAL INFORMATION

No specific information is available. Please refer to Section 2 and 3 for available information on exposure limits and hazards identification.

SECTION 12 - ECOLOGICAL INFORMATION

No specific ecological information is available for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:

PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II  
(Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL

(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL

(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)

SECTION 15 - REGULATORY INFORMATION

SARA 313 INFORMATION:

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

NEW JERSEY RIGHT-TO-KNOW

MATERIAL SAFETY DATA SHEET

11242 061765 604

-----  
NEW JERSEY RIGHT-TO-KNOW

The following non-hazardous ingredients are among the top five components in this product

----- CHEMICAL NAME ----- CAS NUMBER

-----  
PENNSYLVANIA RIGHT-TO-KNOW

No non-hazardous ingredients are present greater than 3%

-----  
INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

-----  
SECTION 16 - OTHER INFORMATION

-----  
The information contained on this MSDS is believed to be reliable and accurate. Due to the changing nature of government information, it is impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.

HMIS RATINGS:

HEALTH: 2\*    FLAMMABILITY: 4    REACTIVITY: 0    PERSONAL PROTECTION: G