


## CHAPTER 15 UNSYMMETRICAL BENDING OF BEAMS

### EXERCISE 58, Page 337

1. Determine the direction and magnitudes of the principal second moments of area of the angle bar shown.



| Section  | $a$                | $y$   | $ay$                  | $ay^2$                 | $i_H$                  |
|----------|--------------------|-------|-----------------------|------------------------|------------------------|
| 1        | $1 \times 10^{-3}$ | 0.195 | $1.95 \times 10^{-4}$ | $3.803 \times 10^{-5}$ | $8.33 \times 10^{-9}$  |
| 2        | $2 \times 10^{-3}$ | 0.1   | $2 \times 10^{-4}$    | $2 \times 10^{-5}$     | $6.667 \times 10^{-6}$ |
| $\Sigma$ | $3 \times 10^{-3}$ | —     | $3.95 \times 10^{-4}$ | $5.803 \times 10^{-5}$ | $6.675 \times 10^{-6}$ |

$$\bar{y} = \frac{\sum ay}{\sum a} = \frac{3.95 \times 10^{-4}}{3 \times 10^{-3}} = 0.1317 \text{ m}$$

$$I_{xx} = \sum ay^2 + \sum i_H = 5.803 \times 10^{-5} + 6.675 \times 10^{-6} = 6.471 \times 10^{-5} \text{ m}^4$$

$$I_{xx} = I_{xx} - (\bar{y})^2 \sum a = 6.471 \times 10^{-5} - (0.1317)^2 \times 3 \times 10^{-3} = 1.268 \times 10^{-5} \text{ m}^4$$

| Section  | $a$                | $x$   | $ax$                 | $ax^2$                 | $i_V$                  |
|----------|--------------------|-------|----------------------|------------------------|------------------------|
| 1        | $1 \times 10^{-3}$ | 0.05  | $5 \times 10^{-5}$   | $2.5 \times 10^{-6}$   | $8.333 \times 10^{-7}$ |
| 2        | $2 \times 10^{-3}$ | 0.105 | $2.1 \times 10^{-4}$ | $2.205 \times 10^{-5}$ | $1.667 \times 10^{-8}$ |
| $\Sigma$ | $3 \times 10^{-3}$ | —     | $2.6 \times 10^{-4}$ | $2.455 \times 10^{-5}$ | $8.5 \times 10^{-8}$   |

$$\bar{x} = \frac{\sum ax}{\sum a} = \frac{2.6 \times 10^{-4}}{3 \times 10^{-3}} = 0.0867 \text{ m}$$

$$I_{yy} = \sum ax^2 + \sum i_v = 2.455 \times 10^{-5} + 8.5 \times 10^{-8} = 2.54 \times 10^{-5} \text{ m}^4$$

$$I_{yy} = I_{yy} - (\bar{x})^2 \sum a = 2.54 \times 10^{-5} - (0.0867)^2 \times 3 \times 10^{-3} = \mathbf{2.849 \times 10^{-6} \text{ m}^4}$$

$$I_{xy} = \sum A h \bar{k} = 1 \times 10^{-3} \times (0.05 - 0.0867) \times (0.195 - 0.1317)$$

$$+ 2 \times 10^{-3} \times (0.105 - 0.0867) \times (0.1 - 0.1317) )$$

$$= -2.323 \times 10^{-6} - 1.16 \times 10^{-6}$$

i.e.  $I_{xy} = -3.483 \times 10^{-6} \text{ m}^4$

$$\tan 2\theta = \frac{2I_{xy}}{I_y - I_x} = \frac{2 \times -3.483 \times 10^{-6}}{2.849 \times 10^{-6} - 1.27 \times 10^{-5}}$$

$$= 0.707$$

from which,  $\theta = \tan^{-1} 0.707 = \mathbf{17.64^\circ}$


$$I_{uu} = \frac{1}{2}(I_x + I_y) + \frac{1}{2}(I_x - I_y)\sec 2\theta$$

$$= 7.775 \times 10^{-6} + 4.9255 \times 10^{-6} \times 1.225$$

i.e.  $I_{uu} = \mathbf{1.381 \times 10^{-5} \text{ m}^4}$

Similarly,  $I_{vv} = \mathbf{1.741 \times 10^{-6} \text{ m}^4}$

**2.** Determine the direction and magnitudes of the principal second moments of area of the section shown.



| Section  | $a$                  | $y$                  | $ay$                   | $ay^2$                  | $i_H$                  |
|----------|----------------------|----------------------|------------------------|-------------------------|------------------------|
| 1        | 0.012                | 0.31                 | $3.72 \times 10^{-3}$  | $1.153 \times 10^{-3}$  | $4 \times 10^{-7}$     |
| 2        | $4.5 \times 10^{-3}$ | 0.15                 | $6.75 \times 10^{-4}$  | $1.0125 \times 10^{-4}$ | $3.375 \times 10^{-5}$ |
| 3        | $3 \times 10^{-3}$   | $7.5 \times 10^{-3}$ | $2.25 \times 10^{-5}$  | $1.6875 \times 10^{-7}$ | $5.625 \times 10^{-8}$ |
| $\Sigma$ | 0.0195               | —                    | $4.418 \times 10^{-3}$ | $1.255 \times 10^{-3}$  | $3.42 \times 10^{-5}$  |

$$\bar{y} = \frac{\sum ay}{\sum a} = \frac{4.418 \times 10^{-3}}{0.0195} = 0.227 \text{ m}$$

$$I_{xx} = \sum ay^2 + \sum i_H = 1.255 \times 10^{-3} + 3.42 \times 10^{-5} = 1.2892 \times 10^{-3} \text{ m}^4$$

$$I_{xx} = I_{xx} - (\bar{y})^2 \sum a = 1.2892 \times 10^{-3} - (0.227)^2 \times 0.0195 = \mathbf{2.844 \times 10^{-4} \text{ m}^4}$$

| Section  | $a$                  | $x$   | $ax$                   | $ax^2$                 | $i_V$                  |
|----------|----------------------|-------|------------------------|------------------------|------------------------|
| 1        | 0.012                | 0.3   | $3.6 \times 10^{-3}$   | $1.08 \times 10^{-3}$  | $3.6 \times 10^{-4}$   |
| 2        | $4.5 \times 10^{-3}$ | 0.3   | $1.35 \times 10^{-3}$  | $4.05 \times 10^{-4}$  | $8.44 \times 10^{-8}$  |
| 3        | $3 \times 10^{-3}$   | 0.408 | $1.224 \times 10^{-3}$ | $4.99 \times 10^{-4}$  | $1 \times 10^{-5}$     |
| $\Sigma$ | 0.0195               | —     | $6.174 \times 10^{-3}$ | $1.984 \times 10^{-3}$ | $3.701 \times 10^{-4}$ |

$$\bar{x} = \frac{\sum ax}{\sum a} = \frac{6.174 \times 10^{-3}}{0.0195} = 0.3166 \text{ m}$$

$$I_{yy} = \sum ax^2 + \sum i_V = 1.984 \times 10^{-3} + 3.701 \times 10^{-4} = 2.354 \times 10^{-3} \text{ m}^4$$

$$I_{yy} = I_{yy} - (\bar{x})^2 \sum a = 2.354 \times 10^{-3} - (0.3166)^2 \times 0.0195 = \mathbf{3.994 \times 10^{-4} \text{ m}^4}$$

$$\begin{aligned}
I_{xy} &= \sum A h \bar{k} = 0.012 \times (0.3 - 0.3166) \times (0.31 - 0.227) \\
&\quad + 4.5 \times 10^{-3} \times (0.3 - 0.3166) \times (0.15 - 0.227) \\
&\quad + 3 \times 10^{-3} \times (0.408 - 0.3166) \times (7.5 \times 10^{-3} - 0.227) \\
&= -1.654 \times 10^{-5} + 5.752 \times 10^{-6} - 6.02 \times 10^{-8}
\end{aligned}$$

i.e.  $I_{xy} = \mathbf{-7.098 \times 10^{-5} \text{ m}^4}$

$$\tan 2\theta = \frac{2I_{xy}}{I_y - I_x} = \frac{-1.4194 \times 10^{-4}}{1.15 \times 10^{-4}}$$

$$= -1.2340$$

from which,

$$2\theta = \tan^{-1}(-1.2340) = -50.99^\circ$$

and

$$\theta = -25.49^\circ$$

$$I_{UU} = \frac{1}{2}(I_x + I_y) + \frac{1}{2}(I_x - I_y)\sec(-50.99^\circ)$$

$$= 3.419 \times 10^{-4} - 1.15 \times 10^{-4} \times 1.589$$


i.e.

$$I_{UU} = 1.592 \times 10^{-4} \text{ m}^4$$

Similarly,

$$I_{VV} = 5.246 \times 10^{-4} \text{ m}^4$$

3. Determine the stresses at the corners and the maximum deflection of a cantilever of length 3 m, loaded at its free end with a concentrated load of 10 kN, as shown.



$$I_{yy} = \frac{BH^3}{36} = \frac{0.2 \times 0.3^3}{36} = 1.5 \times 10^{-4} \text{ m}^4$$


$$I_{VV} = \frac{2 \times 0.3 \times 0.1^3}{12} = 5 \times 10^{-5} \text{ m}^4$$

$$M_{max} = 10 \times 3 = 30 \text{ kN m}$$

$$\theta = 0 \text{ as } I_{xy} = 0$$

$$\beta = \tan^{-1} (-I_{uu} \times \tan \alpha / I_{vv})$$

$$\beta = -60^\circ$$



$\theta_B$

$$u_B = 0 \quad v_B = 0.2 \text{ m}$$

$$\text{At C,} \quad u_C = -0.1 \quad v_C = -0.1$$

$$\begin{aligned}\sigma_B &= \frac{(M \cos \alpha)v}{I_{UU}} + \frac{(M \sin \alpha)u}{I_{VV}} \\ &= +30 \times 10^3 (1154.7 + 0) = +\mathbf{34.64 \text{ MPa}}$$

$$\sigma_c = +30 \times 10^3 (-577.35 - 1000) = -\mathbf{47.32 \text{ MPa}}$$


$$u_A = 0.1 \quad v_A = -0.1$$

$$\sigma_A = 30 \times 10^3 (-577.35 + 1000) = \mathbf{12.68 \text{ MPa}}$$


---

## EXERCISE 59, Page 341


1. If a cantilever of length 3 m, and with a cross-section as shown below, is subjected to a vertically applied downward load at its free end, of magnitude 4 kN, determine the position and value of the maximum bending stress.



To find NA


From Problem 1, Exercise 58,

$$\begin{aligned}\beta &= \tan^{-1} (-I_{uu} \times \tan \theta / I_{vv}) \\ &= \tan^{-1} (-1.381 \times 10^{-5} \times \tan (17.64) / 1.741 \times 10^{-6}) \\ \text{i.e. } \beta &= -68.38^\circ\end{aligned}$$



$$\begin{aligned}\mathbf{u}_B &= x_B \cos \theta + y_B \sin \theta \\ &= (0.1 - 0.0867) \cos 17.64^\circ - 0.1317 \sin 17.64^\circ \\ &= 0.0127 - 0.03991 = -0.0272 \text{ m}\end{aligned}$$

$$\begin{aligned}\mathbf{v}_B &= y_B \cos \theta - x_B \sin \theta \\ &= -0.1255 - 4.03 \times 10^{-3} \\ &= -0.1295 \text{ m}\end{aligned}$$




$$M = 4 \times 3 = 12 \text{ kN m}$$

$$\begin{aligned}\sigma &= \frac{(12 \cos \theta) v_B}{I_{UU}} + \frac{(12 \sin \theta) u_B}{I_{VV}} \\ &= \frac{12 \times 10^3 \times 0.953 \times (-0.1295)}{1.381 \times 10^{-5}} + \frac{12 \times 10^3 \times 0.303 \times (-0.027)}{1.741 \times 10^{-6}} \\ &= -107.24 - 56.39\end{aligned}$$

i.e.

$$\sigma_B = -163.63 \text{ MPa}$$

2. A simply supported beam of length 4 m, and with a cross-section as shown below, is subjected to a centrally placed concentrated load of 20 kN, acting perpendicularly to the xx axis, and through the centroid of the beam. Determine the stress at mid-span at the point B in the cross-section of the beam.



From Problem 2, Exercise 58,

$$\begin{aligned}\beta &= \tan^{-1} (-I_{uu} \tan \theta / I_{vv}) \\ &= \tan^{-1} (-1.592 \times 10^{-4} \tan (-25.49) / 5.246 \times 10^{-4})\end{aligned}$$

i.e.


$$\beta = \tan^{-1} (0.1447) = 8.23^\circ$$

$$u_B = (0.6 - 0.3166) \cos (-25.49) + (0.32 - 0.227) \sin (-25.49)$$

$$= 0.2558 - 0.04 = \mathbf{0.2158 \text{ m}}$$

$$v_B = (0.32 - 0.227) \cos(-25.49) - (0.6 - 0.3166) \sin(-25.49)$$

$$= 0.084 + 0.122 = \mathbf{0.206 \text{ m}}$$



$$\sigma_B = - \left[ \frac{20 \times 10^3 \times \cos(-25.49) \times 0.206}{1.592 \times 10^{-4}} + \frac{20 \times 10^3 \times \sin(-25.49) \times 0.2158}{5.246 \times 10^{-4}} \right],$$

a minus sign because the beam is sagging in mid-span

$$= - [ 23.36 - 3.54 ]$$

i.e.  $\sigma_B = - \mathbf{19.82 \text{ MPa}}$

- 3.** Determine the components of deflection under the load in the directions of the principal axes of bending for the beam of Problem 1 above, given that  $E = 2 \times 10^{11} \text{ N/m}^2$ .

$$\delta_u = \frac{-W \sin \theta l^3}{3EI_v} = \frac{-4 \times 10^3 \times \sin(17.64) \times 3^3}{3 \times 2 \times 10^{11} \times 1.741 \times 10^{-6}}$$

i.e.  $\delta_u = - \mathbf{0.031 \text{ m}}$

$$\delta_v = \frac{-W \cos \theta l^3}{3EI_u} = \frac{-4 \times 10^3 \times \cos(17.64) \times 3^3}{3 \times 2 \times 10^{11} \times 1.381 \times 10^{-5}}$$

i.e.  $\delta_v = - \mathbf{0.0124 \text{ m}}$

- 4.** Determine the components of the central deflection in the directions of the principal axes of bending for the beam of Problem 2 above, given that  $E = 1 \times 10^{11} \text{ N/m}^2$ .

$$\delta_u = \frac{-W \sin \theta l^3}{3EI_v} = \frac{-20 \times 10^3 \times \sin(-25.49) \times 4^3}{48 \times 2 \times 10^{11} \times 5.246 \times 10^{-4}}$$

i.e.  $\delta_u = 2.19 \times 10^{-4} \text{ m}$

$$\delta_v = \frac{-W \cos \theta l^3}{3EI_u} = \frac{-20 \times 10^3 \times \sin(-25.49) \times 4^3}{48 \times 2 \times 10^{11} \times 1.592 \times 10^{-4}}$$

i.e.  $\delta_v = -1.51 \times 10^{-3} \text{ m}$

---