GU1222BSS

Ultimate Flat plate - 2-way plate switch - 2 gangs - stainless steel



Main

| Range of product | Ultimate |
|---------------------------|----------------------|
| Range | Ultimate |
| Device application | Control |
| Aesthetic name | Flat plate |
| Product or component type | Plate switch |
| Control type | Rocker |
| Switch function | 2-way |
| Rated current | 16 AX 230 V AC |
| Colour tint | Stainless steel matt |

Complementary

| Connections - terminals | Screw terminals | |
|-------------------------|-----------------|--|
| Material | Stainless steel | |
| Quantity per set | Set of 1 | |
| Number of gangs | 2 gangs | |
| Device mounting | Wall mounted | |
| Height | 88 mm | |
| Width | 88 mm | |
| Depth | 24 mm | |

Environment

| standards | BS EN 60669-1 | |
|-------------------------|---------------|--|
| IP degree of protection | IP20 | |

Offer Sustainability

| Sustainable offer status | Not Green Premium product | |
|----------------------------------|---|--|
| RoHS (date code: YYWW) | Compliant - since 1244 - Schneider Electric declaration of conformity | |
| REACh | Reference not containing SVHC above the threshold | |
| Product end of life instructions | Need no specific recycling operations | |

Contractual warranty

| Warranty period | 18 months | |
|-----------------|-----------|--|
|-----------------|-----------|--|