GU5214WSS

Ultimate Flat plate - switched fused connection - neon - steel



Main

| Range | Ultimate |
|---------------------------|---------------------------|
| Device application | Protection |
| Aesthetic name | Flat plate |
| Product or component type | Switched fused connection |
| Switch function | Switch |
| Colour tint | Steel White |

Complementary

| Pilot light | Neon indicator red | |
|-------------------------|--------------------|-------------|
| Number of gangs | 1 gang | |
| Material | Steel | |
| Mounting support | Wall mounted | |
| Fixing mode | By screws | |
| Rated current | 13 A 230 V AC | |
| Connections - terminals | Screw terminals | |
| Quantity per set | Set of 1 | |
| Height | 88 mm | |
| Width | 88 mm | |
| Depth | 26 mm | |
| Fuse type | Blade type | |
| | | |

Environment

| IP degree of protection | IP20 | rform. |
|-------------------------|---------|--------|
| standards | BS 1363 | 9 |

Offer Sustainability

| Sustainable offer status | Not Green Premium product | |
|----------------------------------|---|--|
| RoHS (date code: YYWW) | Compliant - since 1244 - Schneider Electric declaration of conformity | |
| REACh | Reference not containing SVHC above the threshold | |
| Product end of life instructions | Need no specific recycling operations | |

Contractual warranty

| Contractual warranty | | |
|----------------------|-----------|--|
| Warranty period | 18 months | |