

# Hayley LED Slim-Line

DOWNLIGHT LUMINAIRES



CE

LED

IP54

IK05

BIM



## Description

Where ceiling voids are shallow our Hayley LED Slim-Line offers exceptional performance where a decorative appearance is required. IP54 as standard.

## Application

- Offices
- Receptions
- Circulation Areas
- Toilets

## Body & Finish

Formed from Die-Cast aluminium complete with a high performance SLM heat sink to ensure life and lumen package.

## Attachments

- Inbuilt PIR
- White Bezel
- Chrome Bezel
- Brushed Aluminium Bezel
- IP65 Bezel



# Hayley LED Slim-Line

DOWNLIGHT LUMINAIRES

## Order Codes

Wattage	Luminous Flux	lm/W	Diameter	Depth	Product Code
11.2 W	1325 lm	118 lm/W	240 mm	21 mm	SGL/LED/1600/HAY/SLIM
12.4 W	1490 lm	120 lm/W	240 mm	21 mm	SGL/LED/1800/HAY/SLIM
14.6 W	1656 lm	113 lm/W	240 mm	21 mm	SGL/LED/2000/HAY/SLIM

Additional lumen outputs are available due to mA ratings and codes may vary from those stated. Please contact us for further details.

## Sizes

- Diameter: 240 mm
- Depth: 21 mm
- Cutout: 225 mm



## Control Gear

Tridonic/OSRAM

- Standard LED
- DALI Dimming LED
- Wireless Bluetooth

## Code Options

- Add /EMG to codes for Emergency
- Add /EMG/ST to codes for Self-Test Emergency
- Add /EMG/AD to codes for Addressable Emergency
- Add /DALI to codes for DALI Dimming
- Add /WH to codes for White Bezel
- Add /CH to codes for Chrome Bezel
- Add /BA to codes for Brushed Aluminium Bezel
- Add /IP65 to codes for IP65 Bezel

## LED Tape

- Tridonic/OSRAM LED Tape
- Colour Temperatures Available: 3000k/4000k/5000k/Tunable/RGB
- All LED data and performance data is taken at an ambient temperature of +25°C

## Main Attributes

- Module efficacy up to 150 lm/W
- 50,000h L90 at 25°C
- Self Cooling
- Colour Rendering Index >80
- 7 Year Guarantee\*
- CE Marked

\* Please refer to the Warranty for more information.

## Photometrics

-