

Hexa LED

SUSPENDED LUMINAIRES



CE

LED

IP20

IK05

TP(a)

UGR<19



Description

The Hexa LED is a unique product, large in size that creates an impressive lighting appearance. Available in 3 sizes this fitting is perfect for areas where a decorative appearance is required with a hexagonal shape.

Application

- Public Areas
- Entrance Foyer
- Open Office Environments.

Body & Finish

Manufactured from 1mm spun steel housing. Powder coated silver as standard.

Attachments

- Integral PIR
- Wire Suspensions
- Rod Suspensions
- Any RAL Colour Available - Please contact us for more information.




Order Codes

Wattage	Luminous Flux	lm/W	Length	Width	Depth	Product Code
24.0 W	3120 lm	130 lm/W	655 mm	567 mm	103 mm	SGL/LED/7/4000/HEX
48.0 W	6240 lm	130 lm/W	1230 mm	1165 mm	103 mm	SGL/LED/13/8000/HEX
72.0 W	9360 lm	130 lm/W	1840 mm	1562 mm	103 mm	SGL/LED/19/12000/HEX

Additional lumen outputs are available due to mA ratings and codes may vary from those stated. Please contact us for further details.

Sizes

- Length: 655/1230/1840 mm
- Width: 567/1165/1562 mm
- Depth: 103 mm



Control Gear

Tridonic/OSRAM

- Standard LED
- DALI Dimming LED
- Wireless Bluetooth

Code Options

- Add /EMG to codes for Emergency
- Add /EMG/ST to codes for Self-Test Emergency
- Add /EMG/AD to codes for Addressable Emergency
- Add /DALI to codes for DALI Dimming
- Add /WI-FI to codes for Wireless Bluetooth
- Add /PIR to codes for Integral PIR
- Add /WS to codes for Wire Suspensions
- Add /RS to codes for Rod Suspensions

LED Boards

- Tridonic/OSRAM LED
- Colour Temperatures Available: 3000k/4000k/5000k
- All LED data and performance data is taken at an ambient temperature of +25°C

Main Attributes

- Module efficacy up to 155 lm/W
- 50,000h L90 at 25°C
- Self Cooling
- Colour Rendering Index >80
- 7 Year Guarantee*
- CE Marked

* Please refer to the Warranty for more information.

Photometrics

-