




SAMUEL HEATH

Product Data Sheet


V527 Exposed Dual Control Shower Kit



Dimension Key




Flow Rates



The flow rate data provided in this document is indicative of each product and is given in an open outlet condition. Installation design, external connections and fittings not supplied may affect the data provided.


Spares Information



Item	Part No.	Description
1	-	Overhead Riser Tube
2	-	Handset
3	-	Handset Cradle
4	-	Grub Screw
5	-	1ft Riser Tube
6	-	Grub Screw
7	-	Riser Rose
8	-	Screw
9	-	Riser Bracket


Item	Part No.	Description
10	-	Diverter Body
11	-	Nut
12	-	Olive
13	VS56080	Diverter Cartridge
14	-	Diverter Top Nut
15	-	Lever

Spares Information




Item	Part No.	Description	Item	Part No.	Description
1	-	Escutcheon	11	-	Lock Nut
2	-	Elbow	12	-	Exposed Bush
3	-	Nut	13	-	Washer
4	-	Nut	14	-	Volume Bush
5	-	Olive	15	-	Washer
6	VS56060	Dual Control Cartridge	16	-	Grub Screw
7	-	Flow Boss	17	-	Cross Top
8	-	Washer	18	-	Grub Screw
9	-	Spindle	19	-	Lever
10	-	Screw			

Installation



1. Assemble the $\frac{1}{2}$ " offset connectors (A) into flush female fittings (B) (fittings not supplied), using a suitable sealant tape on the threads.


Installation



2. Adjust the position of the offset connectors (A) so that they create the correct dimensions for the dual control valve (C).


3. Fix the wall fixing plate (D) using screws (E) and wall plugs provided. Ensure that the wall fixing plate (D) is in line with the offset connectors (A).

Installation




4. Assemble compression nut (F) onto dual control valve (C) captivated olive (J), carry this out on both Hot and Cold inlets.
5. Push escutcheons (K) over offset connectors (A).
6. Slide the dual control valve onto the offset connectors (A) and wall fixing plate (D).
7. Lock in place by tightening grub screws (L) onto wall fixing plate, then tighten compression nuts (F).

Installation



8. Slide boss (O) onto overhead riser tube (P).
9. Slide handset cradle (M) onto overhead riser tube (P) and secure with grub screw (N) at desired position. (Overhead riser tube can be cut down in length to reduce height if required).
10. Assemble the short riser tube (Q), diverter assembly (R) and overhead riser tube (P) to the dual control valve (C) using compression nuts (F) and olives (J).
11. Secure the wall plates (S) using screw (W) and wall plug (T).
12. Slide the peg on boss (O) into wall plate (S) and secure with grub screw (V).


Adjusting the Preset Temperature



This thermostatic mixing valve is factory set to 38°C. It is recommended that showers do not exceed 42°C and never exceed 46°C.

1. Remove the ceramic indice (A).
2. Undo screw (B) and remove cross top (C).
3. Remove spindle (D), rotate anti-clockwise for hotter and clockwise for colder, then reassemble.
4. Reassemble the cross top (C), screw (B) and ceramic indice (A).
5. Test re-set temperature very carefully to avoid injury.
6. The company accepts no liability for injury cause as a result of alteration to the factory set temperature setting.

Maintenance



1. Detach rise tube.
2. Slacken nuts (A) and grub screws (B) to remove the valve from the wall.
3. Unscrew Elbows (C).
4. Remove circlips (D), check valves (E) and filters (F).
5. Rinse the check valves (E) and filters (F) and reassemble the components.

IMPORTANT NOTES

1. Installation should be carried out by a competent engineer, in accordance with water regulations.
2. Before installation, ensure supply pipes are flushed clean. Debris or loose particles will affect the efficiency of the ceramic disc cartridge.
3. For mixer taps, it is recommended that hot & cold pressures are equally balanced.
4. To help maintain the high quality finish, please clean with a soft damp cloth. Do not use abrasive polish or cleaners. Stains may be removed using undiluted washing up liquid.
5. Ceramic cartridges in hard water areas. To prolong the lifespan and reduce servicing periods of your Samuel Heath tap we recommend that a suitable water softener be fitted. Consult your installer/designer for details.
6. Please note that as with all tap and shower ware it will be necessary from time to time for the products to be serviced, this should be carried out by a qualified Plumbing Engineer.

NOTES IMPORTANTES

1. L'installation doit être faite par un ingénieur qualifié, selon les règlements du Service Eau.
2. Avant l'installation, il faut s'assurer que les tuyaux d'approvisionnement sont complètement purgés. Les déchets flottants auront un effet détrimentaire sur l'efficacité de la cartouche céramique.
3. Il est recommandé que les pressions de l'eau chaude et eau froide des mitigeurs et mélangeurs soient maintenues à un niveau égal.
4. Pour conserver la finition de haute qualité, nettoyer avec un chiffon doux et humide. N'employer jamais de la cire et des produits abrasifs. Les tâches peuvent être enlevées à l'aide de liquide vaisselle pur.
5. Cartouches en céramique dans les régions à eau calcaire. Pour prolonger la durée et réduire l'entretien de votre robinetterie Samuel Heath, nous recommandons d'utiliser un adoucisseur d'eau convenable. Veuillez consulter votre installateur/fournisseur pour plus de renseignements.
6. Veuillez noter qu'un entretien sera nécessaire de temps en temps et doit être effectué par un installateur qualifié.

WICHTIGE HINWEISE

1. Installation sollte durch einen kompetenten Fachmann und nach den üblichen Vorschriften ausgeführt werden.
2. Vor Installation Wasserleitung gründlich durchspülen. Verschmutzung wird die Funktion der Kartusche erheblich einschränken.
3. Für Mischbatterien ist es wichtig, daß Wasser mit gleichem Druck eingeführt wird.
4. Um den optimalen Zustand dieses Produktes zu erhalten, wischen Sie es bitte nur mit einem feuchten, weichen Lappen ab. Auf keinen Fall Scheuermittel verwenden. Flecken lassen sich mit unverdünntem Geschirrspülmittel entfernen.
5. Keramikkartuschen in Hartwasserbereichen. Um die Lebensdauer zu verlängern und Wartungszeiten zu reduzieren empfiehlt Samuel Heath den Einsatz eines geeigneten Wasserenthärter. Fragen Sie Ihren Installateur/Designer um Rat.
6. Bitte merken Sie, dass alle Armaturen ab und zu eine Wartung brauchen. Diese soll durch einen kompetenten Installateur ausgeführt werden.

ATENCION

1. La instalación se debe realizar por un fontanero.
2. Antes de la instalación, deben pulgar las tuberías dejando correr el agua por las tuberías para que arrastren los residuos de montaje/obra, con el motivo de que no afecte la eficacia del cartucho de cerámica.
3. Para grupo baño/ducha se recomienda que las presiones del agua caliente y frío sean equilibradas.
4. Para ayudar a mantener el acabado de este producto, limpiar con un paño húmedo suave. No se debe emplear productos abrasivos de baño. Las manchas se pueden quitar empleando líquido lava-vajillas puro.
5. Cartuchos cerámicos en áreas de aguas duras. Para prolongar su vida útil y reducir los periodos de reparación de su grifo Samuel Heath recomendamos la instalación de un descalcificador de agua. Consulte a su instalador para más detalles.
6. Igual que con todo tipo de grifería y duchas, de vez en cuando será necesario llevar a cabo una revisión al producto; esto debería ser realizado por un fontanero calificado.

ATTENZIONE

1. L'impianto deve essere montato da personale tecnico in conformità alle vigenti leggi.
2. Prima dell'installazione assicurarsi che le tubature dell'acqua siano pulite. Detriti o residui di lavorazione compromettono l'efficienza del cartuccio.
3. Per i gruppi, si raccomanda che le pressioni acqua calda e acqua fredda siano ugualmente bilanciate.
4. Per mantenere la finizione di ottima qualità, pulire con un panno soffice e inumidito.
Non usare creme lucidanti e materiali abrasivi. Le macchie potranno essere tolte usando del detersivo per piatti puro.
5. Come con tutti i tipi di rubinetti e docce, di volta in volta è necessario effettuare una revisione al prodotto; questo dovrebbe essere fatto da un idraulico qualificato.

SAMUEL HEATH

Head Office and Customer Service

Leopold Street
Birmingham
England
B12 0UJ

T: +44 (0)121 766 4200
F: +44 (0)121 772 3334

Info@samuel-heath.com
www.samuel-heath.co.uk

US Customer Service

usa@samuel-heath.com
Federal I.D. No. 58-1504682
www.samuel-heath.com

8-40284
Issue: B