

seko

ProFill Eko Tower

Refilling with Automatic Chemical Recharging



Your Choice,
Our Commitment

ProFill Eko Tower

Easy and time saving solution for refilling your scrubber dryer machines

ProFill Eko Tower is the dispensing system that conveniently automatically mixes the right amount of chemical with water preparing ready to use solution to refill scrubber dryer machines.



Automatic magnetic shut off valve with venturi and backflow included

Polyethylene tank horizontally mounted to reduce height 200L capacity

PVC ball valve for better chemical compatibility

Strong base frame carbon steel coated, long life, chemical resistant

Discharge hose nylon braided, for the maximum flexibility and robustness

Spotlight

Quick installation, safe and easy to use


ProFill Eko Tower is the most convenient solution to refill large tank scrubber dryer machines. It is also compact and easy to install.

It comes unmounted to save space and shipping cost. Follow the instruction manual's simple steps in order to have 200lt of ready solution.



Features

- Big tank capacity, 200lt of ready to use solution readily available
- Works without any power supply
- Automatic shut off magnetic float valve and venturi, controls the level of ready to use solution
- ON/OFF inlet ball valve for end of the shift switch OFF
- Strong carbon steel coated frame for longer life
- Polyethylene tank for outstanding chemical compatibility
- Easy, intuitive, low maintenance
- Backflow preventer prevents potable water contamination



Unpack



Install



Ready to Use



ProFill Eko Tower

Water supply connection:	Connection direct to the water source, no electric power or compressed air needed
Type of connection:	3/4" GHT by removing the nut you can connect directly to the ball valve G1/4" connection
Tank capacity:	220L Polyethylene tank
Refilling flow rate:	15.14 l/min (4 g/min) at 2.75 bar (40 psi)
Refilling time:	200L in 13 minutes
Maximum dimensions:	210 cm (H) x 64 cm (W) x 95 cm (D)
Working pressure:	Min 1bar (15 PSI), Max 10bar (150 PSI), Ideal 2.75bar (40 PSI)
Temperature:	Max 120°F (49°C)

Your Choice, Our Commitment

In the modern Globalised world, being a privately owned Company has significant benefits especially for our Customers, our Partners. For over 40 years, SEKO has developed a Global organisation able to take the longer view, manage the pressure of the now, and to plan for the long term, delivering true Partnership for our Customers, with transparency and mutual respect for each other.

Whether it's for our reknown flexibility, our attention to detail, the high-quality products, or just the way we do business, we understand that it's Your Choice to do business with us. It is Our Commitment to fulfill your needs wherever you, our Customers are.



For more information about our portfolio, worldwide locations, approvals, certifications, and local representatives, please visit www.seko.com

As part of a process of on-going product development, SEKO reserves the right to amend and change specifications without prior notice. Published data may be subject to change.

© SEKO, Layout and origin: UK, 850010-ET_en, 11.2017

The SEKO logo is positioned at the bottom right of the page. It features the word "seko" in a bold, lowercase, sans-serif font. The letters are a vibrant blue color. The 's' and 'e' are connected, and the 'k' and 'o' are also connected. The overall design is clean and modern.