



# FORTIS

NON-DIRECTIONAL HOMOGENEOUS  
FLOOR COVERING



## ECOLOGICAL FORMULA



## iGUARD PUR SURFACE



UV cured, cross linked Polyurethane reinforcement which ensures easy cleaning and durability. No additional surface treatment needed for the whole lifetime of the product.

### RECOMMENDED USAGE

- Healthcare • Education
- Offices • Other public areas

### ENVIRONMENTAL ATTRIBUTES

- Phthalate free
- Solvent free
- Heavy metal free
- 100% recyclable
- NO WAX product
- No waste technology

## SPECIFICATIONS

CONSTRUCTION	STANDARDS	FORTIS
<b>DESCRIPTION</b>		
Construction		homogeneous
Total thickness	EN ISO 24346	2.0 mm
Width of roll	EN ISO 24341	2 m
Length of rolls	EN ISO 24341	20 lm
Total weight	EN ISO 23997	2.7 kg/m <sup>2</sup>
<b>CLASSIFICATION</b>		
Product specification	EN 649	✓
European classification	EN 685	Class: 34/43
Residual indentation	EN 433	max. 0.1 mm
Dimensional stability	EN ISO 23999	max 0,4 %
Light fastness	EN ISO 105-B02	grade 6
<b>PERFORMANCE</b>		
Abrasion group	MSZ EN 660-1	T
Fire resistance	EN 13501-1	Bfl-s1
Slip resistance	DIN 51130	R9
	EN 13893	DS
Electrical resistance	EN 1815	< 2 kV
Chemical resistance	EN ISO 26987	✓
Castor chair resistance	EN 425	✓
Surface treatment		iGuard PUR Surface
Hygiene		Bacterial resistant
Seaming method		heat or cold weld

## CONSTRUCTIONS

