


Cable Type: OPGW - 96B1- (AA/AS 148/74 -410,7)

Cross Section:



Structure:	Material	No	Material	No	Material Dia.	
	Fiber	G.652D	96			
SS-Tube	SS	1			Outer Dia	4,80 mm
Al-Tube	Al	1	Inner-Dia	4,80	Outer Dia	8,40 mm
Layer1	20.3% ACS wire	12	AA wire	0	Diameter	2,80 mm
Layer2	20.3% ACS wire	0	AA wire	18	Diameter	2,80 mm

Technical Data:	According to IEC 60794-4-1, IEEE-1138 standards	
Stranding direction of outer layer is right hand (Z-stranding)		
Stranded:Core and layer1 greased	No	
Cable Diameter	19,6 mm	
Cable Weight	943 kg/km	
Supporting Cross Section	222,0 mm ²	
Section of AS Wire	73,9 mm ²	
Section of Al. Part	148,2 mm ²	
Rated Tensile Strength (RTS)	122,9 kN	
Modulus of Elasticity (E-Modulus)	95,8 kN/mm ²	
Minimum EA (Modulus of elasticity x load bearing area)	21,3 kN	
Thermal Elongation Coefficient	17,4 10 ⁻⁶ /°C	
Permissible Maximum Working Stress (40% RTS)	221 N/mm ²	
Everyday Stress (EDS) (15% RTS)	18,4 kN	83 N/mm ²
Max DC Resistance at 20°C	0,183 Ω /km	
Short Time Current (0,2s, 20°C~200°C)	45,31 kA	
Short Circuit Current Capacity I _{2t}	410,7 kA ² s	
Minimum Bending Radius Installation	392 mm	
Minimum Bending Radius Operation	294 mm	
Ratio of RTS to weight	13,3 km	
Temperature Range:	Installation	-10°C ~ +50 °C
	Transportation and Operation	-40°C ~ +80 °C

Remarks: All Sizes and Values are Nominal Values

Diameter tolerance: ± 1% ; Weight tolerance : ± 2%

11.09.2018	HC2018-09-007	OPGW	MK
------------	---------------	------	----

	OPGW Cable Specifications	Serial No:	HC2018-09-007
		Page	2/5

G.652D Fiber

Category	Description	Specifications	
		Before cabling	After cabling
Optical Specifications	Attenuation @1310 nm	≤0.34 dB/km (max.)	≤0.36 dB/km (max.)
	Attenuation @1383±3 nm	≤0.32 dB/km(max.)	≤0.35 dB/km(max.)
	Attenuation @1550 nm	≤0.20 dB/km (max.)	≤0.22dB/km (max.)
	Attenuation @1625 nm	≤0.23dB/km	≤0.25 dB/km
	Zero Dispersion Wavelength	1300~1324 nm	
	Zero Dispersion Slope	≤ 0.092 ps/nm ² -km	
	PMD Link value (M=20cables Q=0.01%) maximum PMD _Q	0.1 ps/√km	
	Cable Cutoff Wavelength (λ _{cc})	≤1260 nm	
	Macro bending Loss (100 turns; Ø50 mm) @1550 nm	≤ 0.05 dB	
	(100 turns; Ø50 mm) @1625 nm	≤ 0.10 dB	
Mode Field Diameter @1310 nm	9.2±0.4µm		
Dimensional Specifications	Cladding Diameter	125 ±0.7µm	
	Core/clad concentricity error	≤0.5µm	
	Cladding Non-Circularity	≤1.0%	
Mechanical Specifications	Proof stress	≥0.69Gpa	

	OPGW Cable Specifications	Serial No:	HC2015-02-007
		Page	3/5

**Color Coding System
for 96 G.652D Optical Fibres acc. To ITU-T G.652**

Fiber color coding

												Group/Binder
1	2	3	4	5	6	7	8	9	10	11	12	1 / blue
Blue,orange,green,brown,greyl,white,red,naturel,yellow, violet,pink,aqua												
Blue,orange,green,brown,greyl,white,red,naturel,yellow, violet,pink,aqua(*)												
(*) With one black ring mark at regular interval.												
1	2	3	4	5	6	7	8	9	10	11	12	2 / red
Blue,orange,green,brown,greyl,white,red,naturel,yellow, violet,pink,aqua												
Blue,orange,green,brown,greyl,white,red,naturel,yellow, violet,pink,aqua(*)												
(*) With one black ring mark at regular interval.												
1	2	3	4	5	6	7	8	9	10	11	12	3 / green
Blue,orange,green,brown,greyl,white,red,naturel,yellow, violet,pink,aqua												
Blue,orange,green,brown,greyl,white,red,naturel,yellow, violet,pink,aqua(*)												
(*) With one black ring mark at regular interval.												
1	2	3	4	5	6	7	8	9	10	11	12	4 / Yellow
Blue,orange,green,brown,greyl,white,red,naturel,yellow, violet,pink,aqua												
Blue,orange,green,brown,greyl,white,red,naturel,yellow, violet,pink,aqua(*)												
(*) With one black ring mark at regular interval.												

	OPGW Cable Specifications	Serial No:	HC2015-02-007
		Page	4/5

TEST REQUIREMENTS FOR OPGW

General

There are different test series to assure the quality of OPGW:

- Routine test (in-process testing according to internal quality plan)
- Factory acceptance test (FAT, witnessed by customer)
- Type test (only in case of a basic new design, repetition in exceptional cases)

OPGW tests shall be in accordance with applicable standards or agreements between purchaser and manufacturer.

As a general rule the tests will be performed according IEC 60794-4-10. However, if necessary tests can be done according to IEEE Std1138.

Type test

Type test may be waived by submitting maker's certificate of the similar product performed in an internationally acknowledged independent test organization or laboratory. If type test should be performed, it will be carried out according to an extra type test procedure reached to an agreement between purchaser and manufacturer.

Routine test

The optical attenuation coefficient on all production cable lengths is measured according to IEC 60793-1-C1C (Back-scattering technique, OTDR). Standard single-mode fibers are measured at 1310nm and at 1550nm. Non-zero dispersion shifted single-mode (NZDS) fibers are measured at 1550nm.

Factory test

Factory acceptance test is carried out on one sample per order in the presence of the customer or his representative. The requirements for quality characteristics are determined by relevant standards and agreed quality plans.

Test items

The following table shows that the test items shall be carried out according to corresponding references.

	OPGW Cable Specifications	Serial No:	HC2015-02-007
		Page	5/5

	Routine	FAT	Type Test	Test Procedure
Test on fibers				
Mode field diameter				IEC 60793-1-45
Geometric parameter				IEC 60793-1-20
Attenuation (OTDR)	●	●		IEC 60793-1-40
Chromatic dispersion				IEC 60793-1-42
Cut-off wavelength (cable cut off)				IEC 60793-1-44
Test on wires before stranding				
Diameter	●	●		IEC61232/ IEC60104
Tensile strength	●	●		IEC61232/ IEC60104
Stress at 1% extension (Only ACS wire)	●	●		IEC61232
Elongation at break	●	●		IEC61232/ IEC60104
Wrapping test (Only AA wire)	●	●		IEC60104
Conductivity	●	●		IEC61232/ IEC60104
Thickness of Al-cladding (Only ACS wire)	●	●		IEC61232/ IEC60104
Torsion test (Only ACS wire)	●	●		IEC61232
Tests on OPGW				
Quality of surface	●	●		IEC 60794-4-10
Direction of lay outer	●	●		IEC 60794-4-10
Lay length	●	●		IEC 60794-4-10
Diameter of cable	●	●		IEC 60794-4-10
Weight of Cable	●	●		IEC 60794-4-10
DC-resistance		●		IEC 60794-4-10
Breaking strength test		●	●	IEC 60794-4-10
Stress Strain Test			●	IEC 60794-4-10
Tensile performance test			●	IEC 60794-4-10
Sheave test			●	IEC 60794-4-10
Aeolian vibration simulation			●	IEC 60794-4-10.
Galloping test			●	IEC 60794-4-10
Creep test			●	IEC 60794-4-10
Temperature cycle test			●	IEC 60794-4-10
Water penetration			●	IEC 60794-4-10
Short circuit current test			●	IEC 60794-4-10
Lightning test			●	IEC 60794-4-10

Notes: The mark "●" means different test items which belongs to different test series.