


## FX 25-95

### Application

For fixed installation indoor/outdoor in the air and on the ground.  
Halogen-free XLPE.

### Basic data

Max continuous temperature            90°C  
 Temperature installation                -20 - +90°C



### Standards

Conductor                                    IEC 60228  
 Construction                                EN 60502-1

E-number	Product	Construction	Area [mm <sup>2</sup> ]	Conductor diameter [mm]	Wall thickness [mm]	Total diameter [mm]	Color [-]	Weight [kg/km]
E0621960	FX25	7x2,14	25	6,42	2,0	10,42	Black	270
E0621965	FX25 T500	7x2,14	25	6,42	2,0	10,42	Black	270
E0621966	FX25 T1000	7x2,14	25	6,42	2,0	10,42	Black	270
E0621970	FX35	7x2,48	35	7,44	2,0	11,44	Black	370
E0621975	FX35 T500	7x2,48	35	7,44	2,0	11,44	Black	370
E0621976	FX35 T1000	7x2,48	35	7,44	2,0	11,44	Black	370
E0621980	FX50	7x2,87	50	8,63	2,0	12,63	Black	485
E0621985	FX50 T500	7x2,87	50	8,63	2,0	12,63	Black	485
E0621986	FX50 T1000	7x2,87	50	8,63	2,0	12,63	Black	485
E0620016	FX95	37x1,80	95	12,6	2,0	16,6	Black	921

All illustrations and specifications of weight, size and dimensions are only indicative