


AMOCharge



Applications:

AMOCharge is a halogen free, hybrid cable, designed for installation where both powersupply and control are needed. The cable meets requirements for several types of communications used in EV-charging stations, including network connected devices. AMOCharge is designed for fixed installation indoors, outdoors and in ground for direct burial or in pipes.

Properties:

Conductor temperatur +90°C
 Temperature range -40 to +90°C
 Voltage Rating Uo/U 0,6/1kV

Standards:

Conductor IEC 60228,2
 Construction IEC 60502-1 IAP
 HD 603 IAP
 Flame retardant EN 50575:2014+A1:2016
 Halogen free IEC 60754-1, -2
 Smoke density IEC 61034-1, -2

CPR Class Dca s2, d2, a1

Construction

Conductor	Class 2 Bare copper
Insulation	XLPE
Outer sheath	HFFR
Marking	AMOCharge 3G/5G[size]+2x2x0,75/1x4x0,5/+Cat7 YY/WW CE [m]
Outer sheath color	Black or customer choice
Bending radius, fixed installation	6x Outer diameter
Communication options	Twisted pairs, Bus, Fiber, Ethernet.
UV	GOOD

Number of cores X conductor cross-section	Nominal outer diameter	Weight	Current rating installation on surface ambient 30°C	GTIN EAN Code	E-Number
	[mm]	[kg/km]	[A]		
5G6+2x2x0,75	19,4	588	52		0462590
5G6+2x2x0,75+Cat7	21,7	655	52		0462600
5G10+1x4x0,75+Cat7	22,1	832	71		0462620
5G16+1x4x0,75	25,0	1086	96		0462630
5G16+1x4x0,75+Cat7	25,0	1083	96		0462640

