



## LS80W-90 GL-5 Mineral

### Product Features:

- Specially designed for limited slip differentials.
- Recommended by Comma for applications requiring an 80W-90 API GL-5 oil.
- To ensure correct oil selection check Comma's latest Application guide in store or online at [CommaOil.com](http://CommaOil.com)

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

### Pack Size Availability:



### Typical Inspection Data:

Density @ 20°C	0.880 g/cm <sup>3</sup>
Viscosity @ 100°C	14.0 cSt
Viscosity @ 40°C	129 cSt
Phosphorus	0.06%
Colour	Brown
Pour Point	-30°C

### Performance Profile:

Recommended by Comma for certain applications with a limited slip differential where an 80W-90 API GL-5 oil is specified. Suitable for use where the following specifications are called for:

API GL-5 LS	Mitsubishi part no: 8149630EX
Ford M2C119-A	

06-06-2016