



## Typical Inspection Data:

|                        |                         |
|------------------------|-------------------------|
| Density @ 20 °C        | 0.853 g/cm <sup>3</sup> |
| Viscosity @ 100 °C     | 13.4 cSt                |
| Viscosity @ 40 °C      | 81 cSt                  |
| Viscosity Index        | 170                     |
| Viscosity CCS @ -30 °C | 5900 cP                 |
| T.B.N.                 | 10.6 mg KOH/g           |
| Sulphated Ash Mass     | 1.1%                    |
| Zinc                   | 0.13%                   |
| Calcium                | 0.11%                   |
| Phosphorus             | 0.11%                   |
| Colour                 | Brown                   |
| Flash Point            | 230 °C                  |
| Pour Point             | -39 °C                  |

## X-Flow Type G 5W-40 Fully Synthetic

### Recommended by Comma for applications requiring:

MB 229.1; VW 502 00, VW 505 00; RN0700, RN0710  
ACEA A3/B4  
API SL CF

### Product Features:

- Fully synthetic 5W-40 oil suitable for petrol and diesel vehicles including those with fuel injected, multivalved and turbo charged engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at [CommaOil.com](http://CommaOil.com).

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

28-02-17