



Pro-VLL 0W-30

Fully Synthetic

Official Approvals:

Approved under VW standard 503 00 and VW standard 506 01

Recommended by Comma for applications requiring:

VW 506 00

Product Features:

- Fully synthetic, high performance fuel-economy promoting engine oil, developed specifically for diesel PD Volkswagen engines running on LongLife Service regime.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Typical Inspection Data:

| | |
|------------------------|--------------|
| Density @ 20 °C | 0.853 |
| Viscosity @ 100 °C | 9.5 cSt |
| Viscosity @ 40 °C | 53 cSt |
| Viscosity Index | 165 |
| Viscosity CCS @ -35 °C | 5900 cP |
| T.B.N. | 9.7 mg KOH/g |
| Sulphated Ash Mass | 1.2% |
| Zinc | 0.14% |
| Calcium | 0.28% |
| Phosphorus | 0.12% |
| Colour | Amber |
| Flash Point | >200°C |
| Pour Point | -42°C |

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

07-12-2017