



Typical Inspection Data:

Density @ 20 °C	0.843 g/cm ³
Viscosity @ 100 °C	6.8 cSt
Viscosity @ 40 °C	35 cSt
Calcium	0.29%
Phosphorus	0.05%
Colour	Brown
Pour Point	-39 °C

Performance Profile:

Recommended by Comma for certain BMW, Ford, Land Rover & VAG group applications and generally where a 75W, API GL4 oil is specified. Suitable for use where the following specifications are called for:

BMW MTF LT-3	VW G 052 726
Ford WSS-M2C200-D2	VW G 052 512
VW G 052 178	Special transmission oil, BOT 350 M3
VW G 060 726	VW G 070 726 A2
VW G 052 171	VW G 052 527 A2

GM 19259104 (BOT 303)

MVMTF Plus 75W

Fully Synthetic

Product Features:

- Fully synthetic manual transmission fluid with excellent bearing and gear protection and proven synchroniser performance.
- Fuel-economy benefits due to low viscosity formulation.
- Exceptional cold temperature performance properties.
- High shear stability for long lasting fluid performance.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

30-11-2017