



Typical Inspection Data:

Density @ 20°C	0.842 g/cm ³
Viscosity @ 100°C	10.2 cSt
Viscosity @ 40°C	55 cSt
Viscosity Index	180
Viscosity CCS @ -35°C	6000 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.11%
Calcium	0.26%
Phosphorus	0.11%
Colour	Brown
Flash Point	230°C
Pour Point	-45°C

Voltech 0W-30

Fully Synthetic

Official Approvals:

Approved by Volvo under 95200377 standard

Recommended by Comma for applications requiring:

ACEA A5/B5; API SL

Product Features:

- Fully synthetic, high performance 0W-30 oil, for modern Volvo petrol and diesel vehicles. Offers improved fuel economy benefits of an ACEA A5/B5 oil.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 24-02-2017