



## X-Flow Type P 5W-30

### Fully Synthetic

**Recommended by Comma for applications requiring:**

ACEA C2; PSA B71 2290

#### Product Features:

- Fully synthetic 5W-30 low SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust after-treatment units that require an ACEA C2 grade.
- To ensure correct oil selection check Comma's latest application guide in store or online at [CommaOil.com](http://CommaOil.com).

#### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

#### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

#### Typical Inspection Data:

Density @ 20°C	0.848 g/cm <sup>3</sup>
Viscosity @ 100°C	10.4 cSt
Viscosity @ 40°C	58 cSt
Viscosity Index	170
Viscosity CCS @ -30°C	5500 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.09%
Calcium	0.19%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

UPDATED: 02-01-2019