



XT2000 15W-40

Semi Synthetic

Recommended by Comma for applications requiring:

MB 229.1; MB 228.3; VW 501 01, VW 505 00
ACEA A3/B4; API SL/CF/CG-4

Product Features:

- Semi synthetic, high performance 15W-40 oil, suitable for petrol and diesel vehicles including those with fuel injected and multivalved engines.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Typical Inspection Data:

Density @ 20°C	0.870 g/cm ³
Viscosity @ 100°C	13.4 cSt
Viscosity @ 40°C	94 cSt
Viscosity Index	143
Viscosity CCS @ -20°C	4000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.4%
Zinc	0.12%
Calcium	0.36%
Phosphorus	0.12%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 15-11-2018