



Eco-T 0W-16

Fully Synthetic

Recommended by Comma for applications requiring:

ILSAC GF-6B, API SP RC

Product Features:

- Fully synthetic, low viscosity engine oil recommended for some of the latest hybrid plug-in and hybrid-electric cars.
- Provides excellent fuel economy and engine durability.
- Specifically developed to minimise low speed pre-ignition (LSPI).
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

Density @ 20°C	0.842 g/cm ³
Viscosity @ 100°C	7.1 cSt
Viscosity @ 40°C	36 cSt
Viscosity Index	164
Viscosity CCS @ -35°C	5200 cP
T.B.N.	8.5 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.14%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-30°C

UPDATED: 02-11-2020