



Eco MB 0W-40

Fully Synthetic

Official Approvals:

Approved under VW standard 502 00 and VW standard 505 00

Recommended by Comma for applications requiring:

ACEA A3/B4; API SN; MB 229.5; MB 226.5; Porsche A40; VW 502.00/505.00; Ford M2C937-A; RN 0700/710

Product Features:

- Fully synthetic, high performance 0W-40 engine oil, for petrol and diesel vehicles including those with fuel injected and multivalved engines.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

Density @ 20°C	0.840 g/cm ³
Viscosity @ 100°C	13.3 cSt
Viscosity @ 40°C	76 cSt
Viscosity Index	179
Viscosity CCS @ -35°C	6000 cP
T.B.N.	10.1 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.12%
Calcium	0.26%
Phosphorus	0.10%
Colour	Brown
Flash Point	230°C
Pour Point	-45°C

UPDATED: 14-01-2021