



Eco-LLP 0W-20

Fully Synthetic

Recommended by Comma for applications requiring:

VW 508 00, VW 509 00; Porsche C20;
ACEA C5

Product Features:

- Designed to deliver excellent fuel economy performance according to VW 508 00/509 00 specification whilst maintaining exceptional wear protection.
- Only suitable for modern engines and not backwardly compatible.
- Recommended for the new 2.0 TFSI 140 kW and 3.0 TDI CR 160 kW VW/Audi engines.
- Suitable for extended drain (Longlife) applications.
- Low SAPS oil to meet the demands of the latest VW 508 00/509 00 specification and to protect exhaust after treatment units.
- Special oil colour and chemical marker technology to ensure use of correct and authentic product.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

| | |
|-----------------------|-------------------------|
| Density @ 20°C | 0.839 g/cm ³ |
| Viscosity @ 100°C | 8.0 cSt |
| Viscosity @ 40°C | 40 cSt |
| Viscosity Index | 178 |
| Viscosity CCS @ -35°C | 5300 cP |
| T.B.N. | 9.8 mg KOH/g |
| Sulphated Ash Mass | 0.8% |
| Zinc | 0.10% |
| Calcium | 0.13% |
| Phosphorus | 0.09% |
| Colour | Slight Green |
| Flash Point | >200°C |
| Pour Point | -57°C |

UPDATED: 14-01-2021