



TransFlow MA 10W-40 Semi Synthetic

Recommended by Comma for applications requiring:

ACEA E4 E7

Deutz IV-10; MAN 3277/3377;

Renault Truck RXD/RLD-2; MTU 3.0; Volvo VDS-3

Official Approvals:

- MB-Approval 228.5

Product Features:

- Designed for most modern commercial vehicles with Diesel Particulate Filter.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

Density @ 20°C	0.857 g/cm ³
Viscosity @ 100°C	14.9 cSt
Viscosity @ 40°C	103 cSt
Viscosity Index	151
Viscosity CCS @ -25°C	6200 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	0.98%
Zinc	0.09%
Calcium	0.33%
Phosphorus	0.08%
Colour	Brown
Flash Point	200°C
Pour Point	-36°C

UPDATED: 14-05-2020