



Typical Inspection Data:

Density @ 20 °C	0.845 g/cm ³
Viscosity @ 100 °C	7.5 cSt
Viscosity @ 40 °C	36 cSt
Calcium	0.02%
Phosphorus	0.04%
Colour	Brown
Pour Point	-45 °C

Performance Profile:

Recommended by Comma for certain VW, Audi, Seat, Ford, Honda Jeep, Mazda, Mercedes-Benz, Mini, Mitsubishi, Nissan, Renault, Subaru, Suzuki, Vauxhall, Opel & Toyota CVT transmissions. Suitable for use where the following specifications are called for:

GM DEX-CVT; GM 1940713; GM 1940714; Ford M2C928-A; WSS-M2C933-A; Mercon C; Nissan NS-1 CVT fluid; Nissan NS-2 CVT fluid; Nissan NS-3 CVT fluid; Mercedes Benz MB 236.20; MG Rover ATF EM-CVT; Subaru Lineartronic High Torque CVT Fluid; Subaru Lineartronic CV-30; Subaru Lineartronic Chain CVTF II; Subaru Lineartronic Chain CVT fluid; Subaru iCVT; Subaru NS-2; BMW/ Mini Cooper CVT Fluid; EZL-799 (ZF CVT V1); Honda HCF-2; Hyundai/ Kia CVT-J1; Hyundai/ Kia SP III (CVT model); Mazda JWS 3320; Dodge/ Jeep; Mopar CVTF +4; Toyota CVT WS (Prius eCVT only); Toyota CVT TC; Toyota CVT FE; Renault Elfmatic CVT; Suzuki CVT Green 1; Suzuki CVT Green 2; Suzuki CVTF TC; Suzuki CVTF 3320; Audi/VW VW G 052 180 A2/ TL 521 80; VW G 052 516/ TL 521 16; Idemitsu CVTS-EX1; Daihatsu Ammix CVT Fluid DC; Daihatsu Ammix CVT Fluid DFC; Daihatsu Fluid TC; Daihatsu Ammix CVT Fluid DFE; Mitsubishi DiaQueen CVTF J1; DiaQueen CVTF J4; DiaQueen CVTF J4+

AQCVT[®] Plus

Fully Synthetic

Product Features:

- High performance CVT fluid for use in a wide range of vehicle makes, including Audi, Toyota, Ford, Mitsubishi, Mercedes Benz, Nissan and many more.
- Provides excellent metal and clutch friction performance.
- Not suitable for Nissan, Toyota and Ford hybrid transmissions.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Modified 31.03.2021