



Typical Inspection Data:

Density @ 20 °C	0.840 g/cm ³
Viscosity @ 100 °C	6.4 cSt
Viscosity @ 40 °C	33 cSt
Phosphorus	0.02%
Colour	Red
Pour Point	-45 °C

Performance Profile:

Recommended by Comma for certain Mercedes, Hyundai, Kia, Vauxhall/Opel and Ford automatic transmissions. Suitable for use where the following specifications are called for:

Nissan Matic W; Nissan Matic J; Nissan Matic D; Nissan Matic K; Nissan Matic S; ATF J3; Honda ATF-Z1; Honda ATF DW-1; N402; Toyota Type T; Volvo 1161540; VW G 052 162; VW G 055 540; ZF TE-ML 11A; ZF TE-ML 11B; GM 1940771; Allison C-4; Aisin Warner AW-1; JWS 3309; JWS 3324 (ATF WS); LA-2634; LT71141; M-1375.4; Mazda FZ; Mercon; Mercon LV; Mercon SP; Mercon V; M-III; NWS 9638 T-5; ATF SP; ATF SP-II; ATF SP-III; ATF SP-IV; Toyota Type T-II; Toyota Type T-IV; Type A suffix A; VW G 055 025; Chrysler MS 7176E (ATF +3); Chrysler MS 9602 (ATF +4); ATF Red-1K; SP-IV-RR; BMW 83 22 2 152 426; BMW 83 22 2 289 720 (ATF3+); BMW 83 22 2 305 397 (ATF3); Honda ATF Type 3.0; Honda ATF Type 3.1; ZF Lifeguardfluid8; Dia Queen ATF-PA; Dexron® II; Dexron® II D; Dexron® IIE; Dexron® IIE + Mercon; Dexron® III; Dexron® III (G); Dexron® (H); Dexron® III + Allison C-4; Dexron® III + Mercon; Dexron® VI; ETL 7045E; ETL 8072B; Ford ESP-M2C166-H; Ford M2C195-A; Ford M2C138-CJ; Ford WSS-M2C202-B; Ford WSS-M2C922-A1; GM 1940767; JWS 3314 + Matic D (1:2); MB 236.10; MB 236.11; MB 236.12; MB 236.14; MB 236.41; MB 236.5; MB 236.6; MB 236.7; MB 236.8; MB 236.9; VW G 052 533; VW G 052 990; VW G 055 005; VW G 060 162; Ford WSS-M2C938-A (power steering)

MVATF PLUS

Fully Synthetic

Product Features:

- Offers excellent frictional stability, anti-shudder & anti-wear properties.
- Suitable for automatic transmissions and power steering systems for many European, American and Asian vehicles.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Modified 15.06.2021

Move Lubricants Ltd. Dering Way, Gravesend, Kent DA12 2QX, England.
Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com www.CommaOil.com

Typical Inspection Data are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.
All products may not be available locally. For more information, contact your local Cosan contact or visit www.CommaOil.com.