



Street LED Lighting IP66

Housing

Electrostatic powder paint coated Aluminum Injection Housing

Glass

5 mm tempered Glass IK08

LED

High CRI MIDPOWER LED with minimum 50.000hrs lifespan (L70)

Optional

- ▶ 30° - 60° - 90° Asimetrik
- ▶ Time Adjusted DIM
- ▶ 0-10V DIM
- ▶ DALI DIM



Product Name	Order Code	Power(W)	CCT(K)	Luminous Flux (lm)	CRI	Voltage V/Hz	Weight
Street LED Lighting	801306	60W	3000K	5630 lm	>80	220VAC	2,91 Kg
Street LED Lighting	801406	60W	4000K	5930 lm	>80	220VAC	2,91 Kg
Street LED Lighting	801606	60W	6500K	5930 lm	>80	220VAC	2,91 Kg
Street LED Lighting	801310	100W	3000K	11130 lm	>80	220VAC	5,81 Kg
Street LED Lighting	801410	100W	4000K	12500lm	>80	220VAC	5,81 Kg
Street LED Lighting	801610	100W	6500K	12500lm	>80	220VAC	5,81 Kg
Street LED Lighting	801315	150W	3000K	14000 lm	>80	220VAC	5,81 Kg
Street LED Lighting	801415	150W	4000K	16000 lm	>80	220VAC	5,81 Kg
Street LED Lighting	801615	150W	6500K	16000 lm	>80	220VAC	5,81 Kg
Street LED Lighting	801320	200W	3000K	19500 lm	>80	220VAC	5,81 Kg
Street LED Lighting	801420	200W	4000K	19890 lm	>80	220VAC	5,81 Kg
Street LED Lighting	801620	200W	6500K	20940 lm	>80	220VAC	5,81 Kg

